


40 dB Fixed Attenuator N Male (Plug) to N Female (Jack) Directional Up to 2.5 GHz Rated to 1000 Watts, Heatsink Body, 1.35 VSWR



SA3N1000-40

Features

- Directional
- DC to 2.5 GHz Frequency Range
- Attenuation 40±2.5 dB
- Max Power 1000 Watts (CW)
- VSWR < 1.35:1

Applications

- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems

Description

Fairview Microwave carries a broad selection of fixed attenuators with a wide range of attenuation levels, frequency ranges, and power dissipation ranges. Also known as RF pads, RF microwave attenuators lower the amplitude of a signal (or attenuate) a known amount. These attenuator pads can be used in a wide variety of applications including reducing a signal level to protect measurement equipment or other circuitry, extending the range of power meters and amplifiers, and impedance matching circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Fairview Microwave carries one of the largest in-stock varieties and ships them same day. The SA3N1000-40 is a 40 dB Fixed Attenuator that operates from DC to 2.5 GHz and is rated to 1000 Watts. The versatile coaxial package uses type N male to type N female connectors. The Black Anodized Aluminum Heatsink body allows for efficient heat dissipation under high power usage conditions.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.5	GHz
Impedance		50		Ohms
Nominal Attenuation		40		dB
Attenuation Accuracy		2.5		dB
VSWR			1.35:1	
Input Power, CW			1	kWatts
derated linearly to 100W at +125°C				
Input Power, Peak			10	kWatts
5µs pulse, 0.5% duty cycle				

Electrical Specification Notes:


Power Sensitivity: 0.0001 dB/dB/W max.//Temperature coefficient: 0.0004 dB/dB/°C max.

Mechanical Specifications

Size

Length	14.8 in [375.92 mm]
Width/Diameter	9 in [228.6 mm]
Height	10.3 in [261.62 mm]
Weight	42.5 lbs [19.28 kg]
Body Material and Plating	Black Anodized Aluminum Heatsink

40 dB Fixed Attenuator N Male (Plug) to N Female (Jack) Directional Up to 2.5 GHz Rated to 1000 Watts, Heatsink Body, 1.35 VSWR



SA3N1000-40

Configuration	
Design	Fixed, Directional
Package Style	Connectorized Module

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Female
Connector Specification	MIL-STD-348A	MIL-STD-348A
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel

Mechanical Specification Notes:
Connectors mate nondestructively with MIL-PRF-39012 connectors.

Environmental Specifications


Temperature	
Operating Range	-55 to +125 deg C
Environmental Specification Notes:	
Designed to meet the environmental requirements of MIL-STD-3933.	

Compliance Certifications (see [product page](#) for current document)


Plotted and Other Data

Notes:

Typical Performance Data



40 dB Fixed Attenuator N Male (Plug) to N Female (Jack) Directional Up to 2.5 GHz Rated to 1000 Watts, Heatsink Body, 1.35 VSWR



SA3N1000-40

40 dB Fixed Attenuator N Male (Plug) to N Female (Jack) Directional Up to 2.5 GHz Rated to 1000 Watts, Heatsink Body, 1.35 VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.


For additional information on this product, please click the following link: [40 dB Fixed Attenuator N Male \(Plug\) to N Female \(Jack\) Directional Up to 2.5 GHz Rated to 1000 Watts, Heatsink Body, 1.35 VSWR SA3N1000-40](https://www.fairviewmicrowave.com/40db-fixed-attenuator-n-male-n-female-1000-watts-sa3n1000-40-p.aspx)

URL: <https://www.fairviewmicrowave.com/40db-fixed-attenuator-n-male-n-female-1000-watts-sa3n1000-40-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

SA3N1000-40 CAD Drawing

40 dB Fixed Attenuator N Male (Plug) to N Female (Jack) Directional Up to 2.5 GHz Rated to 1000 Watts, Heatsink Body, 1.35 VSWR



FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].			
TITLE	DWG NO	SA3N1000-40		CAGE CODE	
		3FKR5			
	CAD FILE	071415	SHEET	SCALE	N/A
				SIZE	A
					5568