

30 dB Fixed Attenuator BNC Male (Plug) to BNC Female (Jack) Up to 6 GHz Rated to 10 Watts, Heatsink Body, 1.3 VSWR



SA6B10W-30

Features

- Bidirectional
- DC to 6 GHz Frequency Range
- Attenuation 30±1 dB
- Max Power 10 Watts (CW)
- VSWR < 1.3:1

Applications

- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems

Description

Fairview Microwave carries a broad selection of fixed attenuators with a wide range of attenuation levels, frequency ranges, and power dissipation ranges. Also known as RF pads, RF microwave attenuators lower the amplitude of a signal (or attenuate) a known amount. These attenuator pads can be used in a wide variety of applications including reducing a signal level to protect measurement equipment or other circuitry, extending the range of power meters and amplifiers, and impedance matching circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Fairview Microwave carries one of the largest in-stock varieties and ships them same day. The SA6B10W-30 is a 30 dB Fixed Attenuator that operates from DC to 6 GHz and is rated to 10 Watts. The versatile coaxial package uses BNC male to BNC female connectors. The Black Anodized Aluminum Heatsink body allows for efficient heat dissipation under high power usage conditions.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
Impedance		50		Ohms
Nominal Attenuation		30		dB
Attenuation Accuracy		1		dB
VSWR			1.3:1	
Input Power, CW			10	Watts
derated linearly to 1W at +125°C				
Input Power, Peak			1	kWatts
5µs pulse, 0.5% duty cycle				

Electrical Specification Notes:

Power Sensitivity: 0.005 dB/dB/W max.//Temperature coefficient: 0.0004 dB/dB/°C max.

Mechanical Specifications

Size

Length	2.64 in [67.06 mm]
Width/Diameter	0.63 in [16 mm]
Height	0 in [0 mm]
Weight	0.089 lbs [40.37 g]
Body Material and Plating	Black Anodized Aluminum Heatsink

30 dB Fixed Attenuator BNC Male (Plug) to
BNC Female (Jack) Up to 6 GHz Rated to
10 Watts, Heatsink Body, 1.3 VSWR



SA6B10W-30

Configuration	
Design	Fixed, Bidirectional
Package Style	Connectorized Module

Connectors

Description	Connector 1	Connector 2
Type	BNC Male	BNC Female
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel	Brass, Nickel

Mechanical Specification Notes:
Connectors mate nondestructively with MIL-PRF-39012 connectors.

Environmental Specifications


Temperature	
Operating Range	-55 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data



30 dB Fixed Attenuator BNC Male (Plug) to
BNC Female (Jack) Up to 6 GHz Rated to
10 Watts, Heatsink Body, 1.3 VSWR



SA6B10W-30

30 dB Fixed Attenuator BNC Male (Plug) to BNC Female (Jack) Up to 6 GHz Rated to 10 Watts, Heatsink Body, 1.3 VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.


For additional information on this product, please click the following link: [30 dB Fixed Attenuator BNC Male \(Plug\) to BNC Female \(Jack\) Up to 6 GHz Rated to 10 Watts, Heatsink Body, 1.3 VSWR SA6B10W-30](https://www.fairviewmicrowave.com/30db-fixed-attenuator-bnc-male-bnc-female-10-watts-sa6b10w-30-p.aspx)

URL: <https://www.fairviewmicrowave.com/30db-fixed-attenuator-bnc-male-bnc-female-10-watts-sa6b10w-30-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

SA6B10W-30 CAD Drawing

30 dB Fixed Attenuator BNC Male (Plug) to BNC Female (Jack) Up to
6 GHz Rated to 10 Watts, Heatsink Body, 1.3 VSWR



BNC MALE

BNC FEMALE

FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].			
TITLE	DWG NO		CAGE CODE		
	SA6B10W-30		3FKR5		
CAD FILE 011415		SHEET		SCALE N/A	SIZE A 5568