

2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF



Features

- 2300 to 2700 MHz and 4900 to 6400 MHz, 19 dBi gain
- 65 deg. beamwidth sector antenna
- 2 + 2 x N-type female connector
- Weather proof - UV resistant PVC radome
- Dual slant polarization (+/- 45 deg.)
- VSWR < 2:1
- 100 W max input power per port

Applications

- Point to point data links (PtP)
- Point to multi-point data links (PtMP)
- 2x2, 4x4 MIMO capability
- WLAN, Wi-Fi 2.4 GHz and 5 GHz, Wireless networks
- DAS, Wi-Fi6 applications
- Smart cities expansion for coverage and IOT / IIOT
- 5G bands - n7, n30, n38, n40, n41, n46, n47, n53, n90, n96, n97, n102
- 4G LTE bands - B7, B30, B33, B38, B40, B41, B46, B47, B69

Description

L-com's HG2364-18XP-065-4NF is a 2.3 GHz to 2.7 GHz, 4.9 GHz to 6.4 GHz WISP sector antenna that is used for IOT, IIOT and various 5G and 4G LTE bands. This antenna features N-type female connector, +/- 45 dual polarization, an UV resistant ABS radome and 16 and 19 dBi gain. Our MIMO antenna supports Wi-Fi's latest frequency band and has a 65-degree beam width.

This HG2364-18XP-065-4NF directional antenna is ideal for cellular or mobile base stations or wireless networking due to its size and directional properties. The gain of the dual-band antenna is 16 dBi for the frequency range of 2.3 GHz to 2.7 GHz and 19 dBi for the frequency range of 4.9 GHz to 6.4 GHz. L-com's WiFi antenna supports low-latency, bandwidth-hungry applications like high-definition video and augmented reality or virtual reality.

Without any extras, the unlicensed WiFi frequency band sector antenna is "future-proof" in terms of network functionality. The N-type female connector on this HG2364-18XP-065-4NF 4-port MIMO antenna has two ports for the first band and two ports for the second band. L-com's sector antennas are suitable for WLAN, PtP, PtMP, 2x2 and 4x4 MIMO capability, 2.4 GHz Wi-Fi, wireless networks, DAS, Wi-Fi6 and smart cities expansion for coverage.

The L-com has the largest in-stock collection of 4-port WISP sector antennas for your critical equipment and power sources. Quickly make your online purchase right now to take advantage of our same-day shipping. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the 2.3 GHz to 2.7 GHz, 4.9 GHz to 6.4 GHz WISP sector antennas as per your requirements.

Configuration

Design	Sector
Band Type	Multi
Radiation Pattern	Directional
Polarization	45 Deg. Slant
Connector Type	N Female
Number of Ports	4
Lightning Protection	DC Grounded

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization HG2364-18XP-

2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF



Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	2,300		6,400	MHz
Impedance		50		Ohms
Input Power			100	Watts

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	2.3-2.7	4.9-6.4				GHz
Gain	16	19				dBi
Horizontal HPBW	70	56				Degrees
Vertical HPBW	7	3				Degrees
Port to Port Isolation	22	25				dB
Front to Back Ratio	28	28				dB
VSWR Max	2:1	2:1				

Mechanical Specifications

Radome Material	PVC
Size	
Length	11.02 in [279.91 mm]
Width	3.15 in [80.01 mm]
Height	35.43 in [899.92 mm]
Mounting Mast Diameter	1.37795 to 1.9685 in [35.00 to 50.00 mm]
Weight	11.03 lbs [5 kg]

Environmental Specifications

Temperature	
Operating Range	-40 to +60 deg C
Wind Survivability	134.216 MPH [216 KPH]

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data



Notes:

2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF



Isolation:





2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF




VSWR:



2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF




2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF



KP-25SX4-65



Unit:mm

2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which

2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

HG2364-18XP-065-4NF



includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

2.3 to 2.7 GHz, 4.9 to 6.4 GHz, 4-port WISP Sector Antenna, 16 and 19 dBi, 65-degree, 2 x 2 N-type female, +/- 45 dual Polarization

L-com CAD Drawing

