

# NTMSD3P303R2

## FETKY™

### P-Channel Enhancement-Mode Power MOSFET and Schottky Diode Dual SO-8 Package

#### Features

- High Efficiency Components in a Single SO-8 Package
- High Density Power MOSFET with Low  $R_{DS(on)}$ , Schottky Diode with Low  $V_F$
- Independent Pin-Outs for MOSFET and Schottky Die Allowing for Flexibility in Application Use
- Less Component Placement for Board Space Savings
- SO-8 Surface Mount Package, Mounting Information for SO-8 Package Provided
- Pb-Free Package is Available

#### Applications

- DC-DC Converters
- Low Voltage Motor Control
- Power Management in Portable and Battery-Powered Products, i.e.: Computers, Printers, PCMCIA Cards, Cellular and Cordless Telephones

#### MOSFET MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                                                                                                                                                                                    | Symbol                                                 | Value                                 | Unit                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------|----------------------------------------|
| Drain-to-Source Voltage                                                                                                                                                                                                                                   | $V_{DS}$                                               | -30                                   | V                                      |
| Gate-to-Source Voltage - Continuous                                                                                                                                                                                                                       | $V_{GS}$                                               | $\pm 20$                              | V                                      |
| Thermal Resistance -<br>Junction-to-Ambient (Note 1)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Continuous Drain Current @ $T_A = 25^\circ\text{C}$<br>Continuous Drain Current @ $T_A = 70^\circ\text{C}$<br>Pulsed Drain Current (Note 4) | $R_{\theta JA}$<br>$P_D$<br>$I_D$<br>$I_D$<br>$I_{DM}$ | 171<br>0.73<br>-2.34<br>-1.87<br>-8.0 | $^\circ\text{C/W}$<br>W<br>A<br>A<br>A |
| Thermal Resistance -<br>Junction-to-Ambient (Note 2)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Continuous Drain Current @ $T_A = 25^\circ\text{C}$<br>Continuous Drain Current @ $T_A = 70^\circ\text{C}$<br>Pulsed Drain Current (Note 4) | $R_{\theta JA}$<br>$P_D$<br>$I_D$<br>$I_D$<br>$I_{DM}$ | 100<br>1.25<br>-3.05<br>-2.44<br>-12  | $^\circ\text{C/W}$<br>W<br>A<br>A<br>A |
| Thermal Resistance -<br>Junction-to-Ambient (Note 3)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Continuous Drain Current @ $T_A = 25^\circ\text{C}$<br>Continuous Drain Current @ $T_A = 70^\circ\text{C}$<br>Pulsed Drain Current (Note 4) | $R_{\theta JA}$<br>$P_D$<br>$I_D$<br>$I_D$<br>$I_{DM}$ | 62.5<br>2.0<br>-3.86<br>-3.10<br>-15  | $^\circ\text{C/W}$<br>W<br>A<br>A<br>A |
| Operating and Storage<br>Temperature Range                                                                                                                                                                                                                | $T_J, T_{stg}$                                         | -55 to<br>+150                        | $^\circ\text{C}$                       |
| Single Pulse Drain-to-Source Avalanche<br>Energy - Starting $T_J = 25^\circ\text{C}$<br>( $V_{DD} = -30\text{ Vdc}$ , $V_{GS} = -4.5\text{ Vdc}$ ,<br>Peak $I_L = -7.5\text{ Apk}$ , $L = 5\text{ mH}$ , $R_G = 25\ \Omega$ )                             | $E_{AS}$                                               | 140                                   | mJ                                     |
| Maximum Lead Temperature for Soldering<br>Purposes, 1/8" from case for 10 seconds                                                                                                                                                                         | $T_L$                                                  | 260                                   | $^\circ\text{C}$                       |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Minimum FR-4 or G-10 PCB, Steady State.
2. Mounted onto a 2" square FR-4 Board  
(1 in sq, 2 oz Cu 0.06" thick single sided), Steady State.
3. Mounted onto a 2" square FR-4 Board  
(1 in sq, 2 oz Cu 0.06" thick single sided),  $t \leq 10$  seconds.
4. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle = 2%.




ON Semiconductor®

<http://onsemi.com>


**MOSFET**  
**-3.05 AMPERES**  
**-30 VOLTS**  
**0.085  $\Omega$  @  $V_{GS} = -10\text{ V}$**

**SCHOTTKY DIODE**  
**3.0 AMPERES**  
**30 VOLTS**  
**420 mV @  $I_F = 3.0\text{ A}$**




(TOP VIEW)

#### MARKING DIAGRAM & PIN ASSIGNMENT



**SO-8**  
**CASE 751**  
**STYLE 18**



E3P303 = Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

| Device        | Package           | Shipping†        |
|---------------|-------------------|------------------|
| NTMSD3P303R2  | SO-8              | 2500/Tape & Reel |
| NTMSD3P303R2G | SO-8<br>(Pb-Free) | 2500/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NTMSD3P303R2

## SCHOTTKY MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                                                 | Symbol             | Value | Unit               |
|------------------------------------------------------------------------------------------------------------------------|--------------------|-------|--------------------|
| Peak Repetitive Reverse Voltage<br>DC Blocking Voltage                                                                 | $V_{RRM}$<br>$V_R$ | 30    | V                  |
| Thermal Resistance – Junction-to-Ambient (Note 5)                                                                      | $R_{\theta JA}$    | 197   | $^\circ\text{C/W}$ |
| Thermal Resistance – Junction-to-Ambient (Note 6)                                                                      | $R_{\theta JA}$    | 97    | $^\circ\text{C/W}$ |
| Thermal Resistance – Junction-to-Ambient (Note 7)                                                                      | $R_{\theta JA}$    | 62.5  | $^\circ\text{C/W}$ |
| Average Forward Current (Note 7)<br>(Rated $V_R$ , $T_A = 100^\circ\text{C}$ )                                         | $I_O$              | 3.0   | A                  |
| Peak Repetitive Forward Current (Note 7)<br>(Rated $V_R$ , Square Wave, 20 kHz, $T_A = 105^\circ\text{C}$ )            | $I_{FRM}$          | 6.0   | A                  |
| Non-Repetitive Peak Surge Current (Note 7)<br>(Surge Applied at Rated Load Conditions, Half-Wave, Single Phase, 60 Hz) | $I_{FSM}$          | 30    | A                  |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

5. Minimum FR-4 or G-10 PCB, Steady State.

6. Mounted onto a 2" square FR-4 Board (1 in sq, 2 oz Cu 0.06" thick single sided), Steady State.

7. Mounted onto a 2" square FR-4 Board (1 in sq, 2 oz Cu 0.06" thick single sided),  $t \leq 10$  seconds.

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted) (Note 8)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                                                                                                                                                              |               |          |          |             |                             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|----------|-------------|-----------------------------|
| Drain-to-Source Breakdown Voltage<br>( $V_{GS} = 0$ Vdc, $I_D = -250$ $\mu\text{Adc}$ )<br>Temperature Coefficient (Positive)                                                | $V_{(BR)DSS}$ | -30<br>– | –<br>–30 | –<br>–      | Vdc<br>mV/ $^\circ\text{C}$ |
| Zero Gate Voltage Drain Current<br>( $V_{DS} = -30$ Vdc, $V_{GS} = 0$ Vdc, $T_J = 25^\circ\text{C}$ )<br>( $V_{DS} = -30$ Vdc, $V_{GS} = 0$ Vdc, $T_J = 125^\circ\text{C}$ ) | $I_{DSS}$     | –<br>–   | –<br>–   | -1.0<br>-25 | $\mu\text{Adc}$             |
| Gate-Body Leakage Current<br>( $V_{GS} = -20$ Vdc, $V_{DS} = 0$ Vdc)                                                                                                         | $I_{GSS}$     | –        | –        | -100        | nAdc                        |
| Gate-Body Leakage Current<br>( $V_{GS} = +20$ Vdc, $V_{DS} = 0$ Vdc)                                                                                                         | $I_{GSS}$     | –        | –        | 100         | nAdc                        |

### ON CHARACTERISTICS

|                                                                                                                                    |              |           |                |                |          |
|------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|----------------|----------------|----------|
| Gate Threshold Voltage<br>( $V_{DS} = V_{GS}$ , $I_D = -250$ $\mu\text{Adc}$ )<br>Temperature Coefficient (Negative)               | $V_{GS(th)}$ | -1.0<br>– | -1.7<br>3.6    | -2.5<br>–      | Vdc      |
| Static Drain-to-Source On-State Resistance<br>( $V_{GS} = -10$ Vdc, $I_D = -3.05$ Adc)<br>( $V_{GS} = -4.5$ Vdc, $I_D = -1.5$ Adc) | $R_{DS(on)}$ | –<br>–    | 0.063<br>0.090 | 0.085<br>0.125 | $\Omega$ |
| Forward Transconductance<br>( $V_{DS} = -15$ Vdc, $I_D = -3.05$ Adc)                                                               | $g_{FS}$     | –         | 5.0            | –              | Mhos     |

### DYNAMIC CHARACTERISTICS

|                              |                                                                         |           |   |     |     |    |
|------------------------------|-------------------------------------------------------------------------|-----------|---|-----|-----|----|
| Input Capacitance            | (V <sub>DS</sub> = -24 Vdc,<br>V <sub>GS</sub> = 0 Vdc,<br>f = 1.0 MHz) | $C_{iss}$ | – | 520 | 750 | pF |
| Output Capacitance           |                                                                         | $C_{oss}$ | – | 170 | 325 |    |
| Reverse Transfer Capacitance |                                                                         | $C_{rss}$ | – | 70  | 135 |    |

8. Handling precautions to protect against electrostatic discharge are mandatory.

# NTMSD3P303R2

## MOSFET ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted) (Note 9)

| Characteristic                                   | Symbol       | Min | Typ | Max | Unit |
|--------------------------------------------------|--------------|-----|-----|-----|------|
| <b>SWITCHING CHARACTERISTICS</b> (Notes 10 & 11) |              |     |     |     |      |
| Turn-On Delay Time                               | $t_{d(on)}$  | –   | 12  | 22  | ns   |
| Rise Time                                        | $t_r$        | –   | 16  | 30  |      |
| Turn-Off Delay Time                              | $t_{d(off)}$ | –   | 45  | 80  |      |
| Fall Time                                        | $t_f$        | –   | 45  | 80  |      |
| Turn-On Delay Time                               | $t_{d(on)}$  | –   | 16  | –   | ns   |
| Rise Time                                        | $t_r$        | –   | 42  | –   |      |
| Turn-Off Delay Time                              | $t_{d(off)}$ | –   | 32  | –   |      |
| Fall Time                                        | $t_f$        | –   | 35  | –   |      |
| Total Gate Charge                                | $Q_{tot}$    | –   | 16  | 25  | nC   |
| Gate–Source Charge                               | $Q_{gs}$     | –   | 2.0 | –   |      |
| Gate–Drain Charge                                | $Q_{gd}$     | –   | 4.5 | –   |      |

## BODY–DRAIN DIODE RATINGS (Note 10)

|                                |                                                                                                                                     |          |        |                |            |               |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|----------|--------|----------------|------------|---------------|
| Diode Forward On–Voltage       | $(I_S = -3.05 \text{ Adc}, V_{GS} = 0 \text{ Vdc})$<br>$(I_S = -3.05 \text{ Adc}, V_{GS} = 0 \text{ Vdc}, T_J = 125^\circ\text{C})$ | $V_{SD}$ | –<br>– | –0.96<br>–0.78 | –1.25<br>– | Vdc           |
| Reverse Recovery Time          | $(I_S = -3.05 \text{ Adc}, V_{GS} = 0 \text{ Vdc}, dI_S/dt = 100 \text{ A}/\mu\text{s})$                                            | $t_{rr}$ | –      | 34             | –          | ns            |
|                                |                                                                                                                                     | $t_a$    | –      | 18             | –          |               |
|                                |                                                                                                                                     | $t_b$    | –      | 16             | –          |               |
| Reverse Recovery Stored Charge |                                                                                                                                     | $Q_{RR}$ | –      | 0.03           | –          | $\mu\text{C}$ |

9. Handling precautions to protect against electrostatic discharge is mandatory.

10. Indicates Pulse Test: Pulse Width = 300  $\mu\text{s}$  max, Duty Cycle = 2%.

11. Switching characteristics are independent of operating junction temperature.

## SCHOTTKY RECTIFIER ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted) (Note 12)

|                                                                                |         |                          |                           |                     |
|--------------------------------------------------------------------------------|---------|--------------------------|---------------------------|---------------------|
| Maximum Instantaneous Forward Voltage                                          | $V_F$   | $T_J = 25^\circ\text{C}$ | $T_J = 125^\circ\text{C}$ | Volts               |
| $I_F = 100 \text{ mAdc}$<br>$I_F = 3.0 \text{ Adc}$<br>$I_F = 6.0 \text{ Adc}$ |         | 0.28<br>0.42<br>0.50     | 0.13<br>0.33<br>0.45      | Volts               |
| Maximum Instantaneous Reverse Current                                          | $I_R$   | $T_J = 25^\circ\text{C}$ | $T_J = 125^\circ\text{C}$ | $\mu\text{A}$<br>mA |
| $V_R = 30 \text{ Vdc}$                                                         |         | 250                      | 25                        |                     |
| Maximum Voltage Rate of Change                                                 | $dV/dt$ | 10,000                   |                           | V/ $\mu\text{s}$    |

12. Indicates Pulse Test: Pulse Width = 300  $\mu\text{s}$  max, Duty Cycle = 2%.

TYPICAL MOSFET ELECTRICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Gate-to-Source Voltage




Figure 5. On-Resistance vs. Drain Current and Gate Voltage







Figure 6. On Resistance Variation with Temperature




**Figure 7. Drain-to-Source Leakage Current vs. Voltage**




**Figure 8. Capacitance Variation**




**Figure 9. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge**



**Figure 10. Resistive Switching Time Variation vs. Gate Resistance**



**Figure 11. Resistive Switching Time Variation vs. Gate Resistance**



**Figure 12. Diode Forward Voltage vs. Current**




Figure 13. Maximum Rated Forward Biased Safe Operating Area




Figure 14. Diode Reverse Recovery Waveform




Figure 15. FET Thermal Response

TYPICAL SCHOTTKY ELECTRICAL CHARACTERISTICS




Figure 16. Typical Forward Voltage




Figure 17. Maximum Forward Voltage




Figure 18. Typical Reverse Current




Figure 19. Maximum Reverse Current




Figure 20. Typical Capacitance




Figure 21. Current Derating

TYPICAL SCHOTTKY ELECTRICAL CHARACTERISTICS




Figure 22. Forward Power Dissipation






Figure 23. Schottky Thermal Response



SCALE 1:1

SOIC-8 NB  
CASE 751-07  
ISSUE AK

DATE 16 FEB 2011





NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.80        | 5.00 | 0.189     | 0.197 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.053     | 0.069 |
| D   | 0.33        | 0.51 | 0.013     | 0.020 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 0.10        | 0.25 | 0.004     | 0.010 |
| J   | 0.19        | 0.25 | 0.007     | 0.010 |
| K   | 0.40        | 1.27 | 0.016     | 0.050 |
| M   | 0°          | 8°   | 0°        | 8°    |
| N   | 0.25        | 0.50 | 0.010     | 0.020 |
| S   | 5.80        | 6.20 | 0.228     | 0.244 |

GENERIC  
MARKING DIAGRAM\*



XXXXXX = Specific Device Code  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

XXXXXX = Specific Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

STYLES ON PAGE 2

|                  |             |                                                                                                                                                                                     |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42564B | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SOIC-8 NB   | PAGE 1 OF 2                                                                                                                                                                         |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**SOIC-8 NB**  
**CASE 751-07**  
**ISSUE AK**

DATE 16 FEB 2011

|                                                                                                                                                                                                   |                                                                                                                                                                                          |                                                                                                                                                                                    |                                                                                                                                                                                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>STYLE 1:</b><br>PIN 1. EMITTER<br>2. COLLECTOR<br>3. COLLECTOR<br>4. EMITTER<br>5. EMITTER<br>6. BASE<br>7. BASE<br>8. EMITTER                                                                 | <b>STYLE 2:</b><br>PIN 1. COLLECTOR, DIE, #1<br>2. COLLECTOR, #1<br>3. COLLECTOR, #2<br>4. COLLECTOR, #2<br>5. BASE, #2<br>6. EMITTER, #2<br>7. BASE, #1<br>8. EMITTER, #1               | <b>STYLE 3:</b><br>PIN 1. DRAIN, DIE #1<br>2. DRAIN, #1<br>3. DRAIN, #2<br>4. DRAIN, #2<br>5. GATE, #2<br>6. SOURCE, #2<br>7. GATE, #1<br>8. SOURCE, #1                            | <b>STYLE 4:</b><br>PIN 1. ANODE<br>2. ANODE<br>3. ANODE<br>4. ANODE<br>5. ANODE<br>6. ANODE<br>7. ANODE<br>8. COMMON CATHODE                                                                           |
| <b>STYLE 5:</b><br>PIN 1. DRAIN<br>2. DRAIN<br>3. DRAIN<br>4. DRAIN<br>5. GATE<br>6. GATE<br>7. SOURCE<br>8. SOURCE                                                                               | <b>STYLE 6:</b><br>PIN 1. SOURCE<br>2. DRAIN<br>3. DRAIN<br>4. SOURCE<br>5. SOURCE<br>6. GATE<br>7. GATE<br>8. SOURCE                                                                    | <b>STYLE 7:</b><br>PIN 1. INPUT<br>2. EXTERNAL BYPASS<br>3. THIRD STAGE SOURCE<br>4. GROUND<br>5. DRAIN<br>6. GATE 3<br>7. SECOND STAGE Vd<br>8. FIRST STAGE Vd                    | <b>STYLE 8:</b><br>PIN 1. COLLECTOR, DIE #1<br>2. BASE, #1<br>3. BASE, #2<br>4. COLLECTOR, #2<br>5. COLLECTOR, #2<br>6. EMITTER, #2<br>7. EMITTER, #1<br>8. COLLECTOR, #1                              |
| <b>STYLE 9:</b><br>PIN 1. EMITTER, COMMON<br>2. COLLECTOR, DIE #1<br>3. COLLECTOR, DIE #2<br>4. EMITTER, COMMON<br>5. EMITTER, COMMON<br>6. BASE, DIE #2<br>7. BASE, DIE #1<br>8. EMITTER, COMMON | <b>STYLE 10:</b><br>PIN 1. GROUND<br>2. BIAS 1<br>3. OUTPUT<br>4. GROUND<br>5. GROUND<br>6. BIAS 2<br>7. INPUT<br>8. GROUND                                                              | <b>STYLE 11:</b><br>PIN 1. SOURCE 1<br>2. GATE 1<br>3. SOURCE 2<br>4. GATE 2<br>5. DRAIN 2<br>6. DRAIN 2<br>7. DRAIN 1<br>8. DRAIN 1                                               | <b>STYLE 12:</b><br>PIN 1. SOURCE<br>2. SOURCE<br>3. SOURCE<br>4. GATE<br>5. DRAIN<br>6. DRAIN<br>7. DRAIN<br>8. DRAIN                                                                                 |
| <b>STYLE 13:</b><br>PIN 1. N.C.<br>2. SOURCE<br>3. SOURCE<br>4. GATE<br>5. DRAIN<br>6. DRAIN<br>7. DRAIN<br>8. DRAIN                                                                              | <b>STYLE 14:</b><br>PIN 1. N-SOURCE<br>2. N-GATE<br>3. P-SOURCE<br>4. P-GATE<br>5. P-DRAIN<br>6. P-DRAIN<br>7. N-DRAIN<br>8. N-DRAIN                                                     | <b>STYLE 15:</b><br>PIN 1. ANODE 1<br>2. ANODE 1<br>3. ANODE 1<br>4. ANODE 1<br>5. CATHODE, COMMON<br>6. CATHODE, COMMON<br>7. CATHODE, COMMON<br>8. CATHODE, COMMON               | <b>STYLE 16:</b><br>PIN 1. EMITTER, DIE #1<br>2. BASE, DIE #1<br>3. EMITTER, DIE #2<br>4. BASE, DIE #2<br>5. COLLECTOR, DIE #2<br>6. COLLECTOR, DIE #2<br>7. COLLECTOR, DIE #1<br>8. COLLECTOR, DIE #1 |
| <b>STYLE 17:</b><br>PIN 1. VCC<br>2. V2OUT<br>3. V1OUT<br>4. TXE<br>5. RXE<br>6. VEE<br>7. GND<br>8. ACC                                                                                          | <b>STYLE 18:</b><br>PIN 1. ANODE<br>2. ANODE<br>3. SOURCE<br>4. GATE<br>5. DRAIN<br>6. DRAIN<br>7. CATHODE<br>8. CATHODE                                                                 | <b>STYLE 19:</b><br>PIN 1. SOURCE 1<br>2. GATE 1<br>3. SOURCE 2<br>4. GATE 2<br>5. DRAIN 2<br>6. MIRROR 2<br>7. DRAIN 1<br>8. MIRROR 1                                             | <b>STYLE 20:</b><br>PIN 1. SOURCE (N)<br>2. GATE (N)<br>3. SOURCE (P)<br>4. GATE (P)<br>5. DRAIN<br>6. DRAIN<br>7. DRAIN<br>8. DRAIN                                                                   |
| <b>STYLE 21:</b><br>PIN 1. CATHODE 1<br>2. CATHODE 2<br>3. CATHODE 3<br>4. CATHODE 4<br>5. CATHODE 5<br>6. COMMON ANODE<br>7. COMMON ANODE<br>8. CATHODE 6                                        | <b>STYLE 22:</b><br>PIN 1. I/O LINE 1<br>2. COMMON CATHODE/VCC<br>3. COMMON CATHODE/VCC<br>4. I/O LINE 3<br>5. COMMON ANODE/GND<br>6. I/O LINE 4<br>7. I/O LINE 5<br>8. COMMON ANODE/GND | <b>STYLE 23:</b><br>PIN 1. LINE 1 IN<br>2. COMMON ANODE/GND<br>3. COMMON ANODE/GND<br>4. LINE 2 IN<br>5. LINE 2 OUT<br>6. COMMON ANODE/GND<br>7. COMMON ANODE/GND<br>8. LINE 1 OUT | <b>STYLE 24:</b><br>PIN 1. BASE<br>2. EMITTER<br>3. COLLECTOR/ANODE<br>4. COLLECTOR/ANODE<br>5. CATHODE<br>6. CATHODE<br>7. COLLECTOR/ANODE<br>8. COLLECTOR/ANODE                                      |
| <b>STYLE 25:</b><br>PIN 1. VIN<br>2. N/C<br>3. REXT<br>4. GND<br>5. IOUT<br>6. IOUT<br>7. IOUT<br>8. IOUT                                                                                         | <b>STYLE 26:</b><br>PIN 1. GND<br>2. dv/dt<br>3. ENABLE<br>4. ILIMIT<br>5. SOURCE<br>6. SOURCE<br>7. SOURCE<br>8. VCC                                                                    | <b>STYLE 27:</b><br>PIN 1. ILIMIT<br>2. OVLO<br>3. UVLO<br>4. INPUT+<br>5. SOURCE<br>6. SOURCE<br>7. SOURCE<br>8. DRAIN                                                            | <b>STYLE 28:</b><br>PIN 1. SW_TO_GND<br>2. DASIC_OFF<br>3. DASIC_SW_DET<br>4. GND<br>5. V_MON<br>6. VBULK<br>7. VBULK<br>8. VIN                                                                        |
| <b>STYLE 29:</b><br>PIN 1. BASE, DIE #1<br>2. EMITTER, #1<br>3. BASE, #2<br>4. EMITTER, #2<br>5. COLLECTOR, #2<br>6. COLLECTOR, #2<br>7. COLLECTOR, #1<br>8. COLLECTOR, #1                        | <b>STYLE 30:</b><br>PIN 1. DRAIN 1<br>2. DRAIN 1<br>3. GATE 2<br>4. SOURCE 2<br>5. SOURCE 1/DRAIN 2<br>6. SOURCE 1/DRAIN 2<br>7. SOURCE 1/DRAIN 2<br>8. GATE 1                           |                                                                                                                                                                                    |                                                                                                                                                                                                        |

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42564B</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOIC-8 NB</b>   | <b>PAGE 2 OF 2</b>                                                                                                                                                                  |

**onsemi** and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)