



BNC Male Open Circuit Connector Cap with 2.7 Inch Chain

Shorts and Caps Technical Data Sheet

M39012/25-0007

Features

- · Protects against dust and contaminants
- · Protects against physical damage

· Silver Plated Body

Applications

- General Purpose Laboratory Use
- · Test and Measurement

Description

Pasternack's M39012/25-0007 connector dust cap has a BNC interface and a male gender. Our BNC male dust cap is a non-shorting design with a silver plated body to ensure durability. The Pasternack non-shorting BNC connector cap is part of over 40,000 RF, microwave and millimeter wave products that ship the same day.

RF connector dust caps are essential for precision connectors, protecting them from dust, corrosion and potential damage especially to test and measurement equipment. Specific RF connector cap models come with a chain to prevent loss or misplacement. Internal short connector cap versions are available to protect equipment from a spike in current caused by electrostatic discharge (ESD).

Mechanical Specifications

Configuration

Connector BNC Male Non-Shorting Chain Option 2.7 in Chain

Description	Material	Plating
Body	Brass	Silver QQ-S-365

Size	
Length	0.67 in [17.02 mm]
Width	3.9 in [99.06 mm]
Height	0.6 in [15.24 mm]
Weight	0.25 lbs [113.4 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male Open Circuit Connector Cap with 2.7 Inch Chain M39012/25-0007

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451





BNC Male Open Circuit Connector Cap with 2.7 Inch Chain

Shorts and Caps Technical Data Sheet

M39012/25-0007

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

BNC Male Open Circuit Connector Cap with 2.7 Inch Chain from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male Open Circuit Connector Cap with 2.7 Inch Chain M39012/25-0007

URL: https://www.pasternack.com/non-shorting-bnc-male-with-2.7-inch-chain-m39012-25-0007-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

M39012/25-0007 CAD Drawing BNC Male Open Circuit Connector Cap with 2.7 Inch Chain ш INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 ⋖ 1 OF APPROVED AGANWANI BNC Male Open Circuit Connector Cap with 2.7 Inch Chain M39012/25-0007 NONE \bigoplus CHANGED BY **PSRINIVAS PASTERNACK** ITEM NO Website: www.Pasternack.com Phone: 1.866.727.8376 | 1.949.261.1920 an INFINIT® brand 06/27/2023 DATE **PSRINIVAS** N REVISION CAGE CODE DRAWN BY INITIAL RELEASE 53919 DESCRIPTION SIZE ⋖ ALL DIMENSIONS ARE FOR REFERENCE ONLY
AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES
MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY ± 1/32 ANGLES ± 1° \$12 [305] = +1 [25] / 0 >12 [305] \$60 [1524] = +2 [51] / -0 >60 [1524] = +2 [61] / -0 >120 [3048] \$300 [7620] = +6 [102] / -0 >300 [7620] = +5% / -0 UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILL IMETERS FRACTIONS CABLE LENGTH TOLERANCES: [17.02] .670 REV ⋖ $X = \pm .2$ [5] $XX = \pm .02$ [0.5] $XXX = \pm .005$ [0.13] ZONE THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TOU.S. LAW PROHIBITED. 2.700 [68.58] 1. QUALIFIED SUPPLIER CAGE CODE: 00795 2 I.D. Ø.520[13.21]-9 NOTES:-Ш О В ⋖ ш \circ