



2 Way N Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts

Power Dividers Technical Data Sheet

PE2092

Features

- 2-Way Power Divider
- Wilkinson Design
- 0.69 to 2.7 GHz Frequency Range
- Max Power 10 Watts (CW)
- Insertion Loss < 0.5 dB
- Isolation > 22 dB

Applications

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

Description

Pasternack carries a wide selection of power dividers to fit your needs. These components are essential in many systems, allowing the combination of multiple signals or splitting of a single signal into multiple signals with equal magnitude and phase. Pasternack's resistive and Wilkinson power dividers come with excellent performance featuring minimal loss, high isolation and low VSWR. They are available in both narrow and broad bandwidths with a variety of connector types such as 2.92mm, BNC, N and SMA.

The PE2092 is a 2-way Wilkinson power divider that operates from 0.69 to 2.7 GHz and can handle up to 10 Watts (CW) with 0.5 dB max insertion loss and 22 dB min isolation. The package interface uses N female connectors and is REACH and RoHS compliant.

Electrical Specifications

Design	Wilkinson
Number of Output Ports	2

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.69		2.7	GHz
Impedance		50		Ohms
Input VSWR			1.25:1	
Output VSWR			1.2:1	
Insertion Loss			0.5	dB
Isolation	22			dB
Amplitude Balance			0.2	dB
Phase Balance			3	Degrees
Input Power (CW)			10	Watts

Electrical Specification Notes:
Max input power rated for load VSWR better than 2.0:1.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Way N Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts PE2092](#)



2 Way N Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts

Power Dividers Technical Data Sheet

PE2092

Mechanical Specifications

Size

Length	1.97 in [50.04 mm]
Width	2 in [50.8 mm]
Height	0.83 in [21.08 mm]
Weight	0.37 lbs [167.83 g]

Housing Material and Plating

Aluminum

Configuration

Package Type	Connectorized
Input Connector	N Female
Input Connector Specification	MIL-STD-348
Output Connectors	N Female
Output Connectors Specification	MIL-STD-348

Environmental Specifications

Temperature

Operating Range	-55 to +85 deg C
-----------------	------------------

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	
REACH Compliant	12/17/2015

Plotted and Other Data

Notes:

2 Way N Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Way N Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts PE2092](http://www.pasternack.com/2-way-n-wilkinson-power-divider-690-mhz-2.7-ghz-10-watts-pe2092-p.aspx)

URL: <http://www.pasternack.com/2-way-n-wilkinson-power-divider-690-mhz-2.7-ghz-10-watts-pe2092-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE2092 CAD Drawing

2 Way N Wilkinson Power Divider From 690 MHz to 2.7 GHz Rated at 10 Watts



STANDARD TOLERANCES
DECIMAL

.XX ±0.10

.XXX ±0.05

*STANDARD TOLERANCES APPLY
ONLY TO DIMENSIONS IN INCHES

PE PASTERNAK®
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE2092

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

FSCM NO. 53919

CAD FILE 051016

SCALE N/A

SIZE A

3045