

2 Way N Power Divider from 617 MHz to 2.7 GHz Rated at 30 Watts



Power Dividers Technical Data Sheet

PE20DV1032A

Features

- 30 watt CW Rating
- 617 to 2,700 MHz
- High Power

- N Type Female Connector
- Mounting Bracket

Applications

- Indoor/Outdoor Use (IP67)
- Base Station
- 4G/LTE/AWS/PCS/PMR/UMTS/
- TETRA/WiFi/WiMAX
- Distributed Antenna Systems (DAS)

Wireless Infrastructure

Description

The PE20DV1032A is a 2 way Wilkinson Power Divider with N Type Female connectors rated to 30 watt CW.

Pasternack's family of Power Dividers are designed without solder joints and a unique construction allows for exceptional performance within the 617 to 2,700 MHz frequency range. They are offered in a range of output port options to allow flexibility in the design of your DAS system. They can be used indoor or outdoor as they meet the moisture requirements of IP67. They are available in two different connector types: N and Mini DIN 4.1/9.5.

Electrical Specifications

Design Wilkinson
Number of Output Ports 2

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.617		2.7	GHz
Impedance		50		Ohms
Input VSWR			1.3:1	
Output VSWR			1.2:1	
Insertion Loss			0.5	dB
Isolation	21			dB
Input Power (CW)			30	Watts
Reverse Power (CW)			0.4	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 Way N Power Divider from 617 MHz to 2.7 GHz Rated at 30 Watts PE20DV1032A

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451



2 Way N Power Divider from 617 MHz to 2.7 GHz Rated at 30 Watts



Power Dividers Technical Data Sheet

PE20DV1032A

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	0.617 to 0.698	0.698 to 2.7				GHz
Input VSWR, Max	1.3:1	1.2:1				
Output VSWR, Max	1.2:1	1.2:1				
Insertion Loss, Max	0.3	0.5		A \		dB
Isolation, Min	21	22				dB

Mechanical Specifications

Housing Material and Plating Aluminum, Chem Film

Configuration

Package Type Connectorized Input Connector N Female Output Connectors N Female Ingress Protection (IP) Rating IP67

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

2 Way N Power Divider from 617 MHz to 2.7 GHz Rated at 30 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 Way N Power Divider from 617 MHz to 2.7 GHz Rated at 30 Watts PE20DV1032A

URL: https://www.pasternack.com/2-way-n-power-divider-2.7-ghz-pe20dv1032a-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE20DV1032A CAD Drawing

2 Way N Power Divider from 617 MHz to 2.7 GHz Rated at 30 Watts

