



4-Way SMA Power Divider 1-2GHz 30W

Power Dividers Technical Data Sheet

PE20DV2103

Features

- Ultra Wide Band Operation
- 30 watt CW Rating
- 1 to 2 GHz
- SMA Female Connector
- Meets Standards for Humidity, Shock, Vibration, Altitude

Applications

- Communications Systems
- Amplifier Systems
- Amplifier Power Dividing
- Aerospace/Aviation
- Defense Applications

Description

PE20DV2103 is a passive 4 way RF Power Divider with 50 ohm SMA female connectors operating from 1 to 2 GHz, with a max input power of 30 watts. The PE20DV2103 has min 20 dB Isolation, 0.6 dB Maximum Insertion loss and a Max VSWR of 1.25:1; along with a phase balance of ± 3 degrees and an amplitude balance of ± 0.3 dB. The RF Divider operates in a temperature range from -45°C to 85°C and is rated for Humidity, Shock, Vibration, and Altitude. Power dividers have many applications and so perform many valuable functions within the RF/Microwave world. Examples are antenna beam forming, taps for cable distributed systems combining feeds to and from antennae.

Electrical Specifications

Design	Standard
Number of Output Ports	4

Description	Minimum	Typical	Maximum	Units
Frequency Range	1		2	GHz
Impedance		50		Ohms
Input VSWR		1.2:1	1.25:1	
Output VSWR		1.15:1	1.2:1	
Insertion Loss		0.35	0.6	dB
Isolation	20	21.5		dB
Amplitude Balance		0.2	0.3	dB
Phase Balance		2	3	Degrees
Input Power (CW)			30	Watts
Reverse Power (CW)			2	Watts
Input Power (Peak)			300	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [4-Way SMA Power Divider 1-2GHz 30W PE20DV2103](#)



4-Way SMA Power Divider 1-2GHz 30W

Power Dividers Technical Data Sheet

PE20DV2103

Mechanical Specifications

Size

Length	0 in [0 mm]
Width	0 in [0 mm]
Height	0 in [0 mm]
Weight	0.13 lbs [58.97 g]

Finish

Housing Material and Plating	Gray Aluminum
------------------------------	------------------

Configuration

Input Connector	SMA Female
-----------------	------------

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-50 to +105 deg C

Humidity

Shock	100% RH at 35°C, 95%RH at 40°C
Vibration	20G for 11msec half sine wave, 3 axis both directions
Altitude	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis 30,000ft. Epoxy Sealed, 60,000ft. 1psi min Hermetically Sealed

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

4-Way SMA Power Divider 1-2GHz 30W from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [4-Way SMA Power Divider 1-2GHz 30W PE20DV2103](#)

URL: <https://www.pasternack.com/4-way-sma-power-divider-2-ghz-pe20dv2103-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE20DV2103 CAD Drawing
4-Way SMA Power Divider 1-2GHz 30W

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/1/2021	S. PONG



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		TOLERANCES:		X = ±.2 [5.08] .XX = ±.02 [.51] .XXX = ±.005 [.13] ANGLES ± 1° CABLE LENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5% / -0		ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	
PE PASTERNAK® an INFINITE brand Pasternack Enterprises, Inc. P.O.Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com		SIZE A		CAGE CODE 53919	DRAWN BY K.DANG	ITEM NO. PE20DV2103	REV A
THIRD-ANGLE PROJECTION		  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.		SHEET 1 OF 1		SCALE N/A	

LABEL

DV2103
YYWW

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE
WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.