



MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE33575/HS

Configuration

- Connector 1: MCX Plug Right Angle
- Connector 2: BNC Female Bulkhead
- Cable Type: RG188

Features

- Max Frequency 1 GHz
- PTFE Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE33575/HS MCX plug right angle to BNC female bulkhead cable using RG188 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack MCX to BNC cable assembly has a plug to female gender configuration with 50 ohm flexible RG188 coax. The PE33575/HS MCX plug to BNC female cable assembly operates to 1 GHz. The right angle MCX interface on the RG188 cable allows for easier connections in tight spaces. Our RF cable assembly with BNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1,000	MHz
VSWR			1.5:1	
Operating Voltage (AC)			250	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	500	1,000	MHz
Insertion Loss (Typ.)	0.025	0.05	0.125	0.25	0.5	dB/ft
	0.08	0.16	0.41	0.82	1.64	dB/m

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink PE33575/HS](#)



MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE33575/HS

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.05xSQRT(fGHz) dB for the right angle connector and 0.1 dB for the straight connector.

Mechanical Specifications

Cable Assembly

Weight	0.065 lbs [29.48 g]
Cable	
Cable Type	RG188
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	1
Shield Layer 1	Silver Plated Copper Braid
Jacket Material	PTFE, White
Jacket Diameter	0.11 in [2.79 mm]

Connectors

Description	Connector 1	Connector 2
Type	MCX Plug Right Angle	BNC Female Bulkhead
Specification	CECC 22220	
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 µin minimum	30 µin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 µin minimum	100 µin minimum

Environmental Specifications

Temperature

Operating Range -40 to +60 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink PE33575/HS](#)



MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE33575/HS

How to Order

Part Number Configuration:

PE33575/HS

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE33575/HS-12 = 12 inches long cable
PE33575/HS-100cm = 100 cm long cable

MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to BNC Female Bulkhead Cable Using RG188 Coax with HeatShrink PE33575/HS](#)

URL: <https://www.pasternack.com/mcx-plug-right-angle-to-bnc-female-bulkhead-cable-using-rg188-with-heatshrink-pe33575-hs-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE33575/HS CAD Drawing

MCX Plug Right Angle to BNC Female Bulkhead Cable
Using RG188 Coax with HeatShrink

