



BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length

RF Cable Assemblies Technical Data Sheet


PE34446-50CM

Configuration

- Connector 1: BNC Female
- Connector 2: SHV Plug
- Cable Type: RG58

Features

- Max Frequency 300 MHz
- Shielding Effectivity > 45 dB
- 65.9% Phase Velocity
- PVC (NC) Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE34446-50CM BNC female to SHV plug 50 cm cable using RG58 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to SHV cable assembly has a female to plug gender configuration with 50 ohm flexible RG58 coax. The PE34446-50CM BNC female to SHV plug cable assembly operates to 300 MHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length PE34446-50CM](#)



BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length

RF Cable Assemblies Technical Data Sheet

PE34446-50CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		300	MHz
VSWR			1.4:1	
Velocity of Propagation		65.9		%
RF Shielding	45			dB
Capacitance		30.8 [101.05]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	300		MHz
Insertion Loss (Typ.)	0.1	0.15	0.23	0.25		dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1*SQRT(FGHz) dB per connector.

Mechanical Specifications

Cable Assembly

Length*	19.68 in [499.87 mm]
Weight	0.099 lbs [44.91 g]

Cable

Cable Type	RG58
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Tin
Dielectric Type	PE
Number of Shields	1
Shield Layer 1	Tinned Copper Braid
Jacket Material	PVC (NC), Black
Jacket Diameter	0.195 in [4.95 mm]
One Time Minimum Bend Radius	2 in [50.8 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length PE34446-50CM](#)



BNC Female to SHV Plug Cable Using
RG58 Coax In 50 CM Length

RF Cable Assemblies Technical Data Sheet

PE34446-50CM

Connectors

Description	Connector 1	Connector 2
Type	BNC Female	SHV Plug
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification		30μ in. minimum
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification		100μ in. minimum
Coupling Nut Material and Plating		Brass, Nickel
Coupling Nut Plating Specification		100μ in. minimum

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length PE34446-50CM](#)



BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length

RF Cable Assemblies Technical Data Sheet

PE34446-50CM

How to Order

Part Number Configuration:

PE34446

- xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE34446-12 = 12 inches long cable
PE34446-100cm = 100 cm long cable

BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length PE34446-50CM](https://www.pasternack.com/bAc-female-to-shv-plug-cable-50-cm-leAgth-usiAg-rg58-pe34446-50cm-p.aspx)


URL: <https://www.pasternack.com/bAc-female-to-shv-plug-cable-50-cm-leAgth-usiAg-rg58-pe34446-50cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE34446-50CM CAD Drawing

BNC Female to SHV Plug Cable Using RG58 Coax In 50 CM Length

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	11/10/2021	A. GANWANI



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS				TOLERANCES:				THIRD-ANGLE PROJECTION			
X = ± .2				[.008]				FRACTIONS			
.XX = ± .02				[.51]				± 1/32			
.XXX = ± .005				[.13]				ANGLES ± 1°			
CABLE LENGTH (L) TOLERANCES:											
L ≤ 12 [305]								± .1 [25] / -0			
12 [305] < L ≤ 60 [1524]								± .2 [51] / -0			
60 [1524] < L ≤ 120 [3048]								± .4 [102] / -0			
120 [3048] < L ≤ 300 [7620]								± .6 [152] / -0			
300 [7620] < L								± .5% / -0			
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.								ITEM NO.			
SIZE A				CAGE CODE 53919				DRAWN BY K.DANG			
								PE34446			
								REV A			
PASTERNAK® an INFINITE brand								THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.			
Pasternack Enterprises, Inc. P.O.Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com								SHEET 1 OF 1 SCALE N/A			

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.