



## SMA Male to SMA Male Right Angle Semi-Flexible Precision Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS

### TECHNICAL DATA SHEET

**PE39439-12**

#### Hand Formable SMA Male to SMA Male Right Angle Semi-Flexible Precision Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS

Pasternack's formable cable assemblies are hand formable semi-rigid replacements that are an alternative to costly preformed assemblies. The formable semi-rigid cable alternatives are dimensionally and electrically similar to their semi-rigid counterpart and have a tinned-copper-braid outer shield that provides excellent RF shielding. The hand formable cable assemblies from Pasternack do not require special tooling to shape or reshape the assemblies and can replace standard semi-rigid versions. The assemblies are available with or without a PVC jacket and are RoHS compliant,

- Dimensionally and electrically the same as standard, solid outer conductor semi-rigid coax
- Cable may be formed by hand and does not require special tools to bend
- May be formed more than once without damaging the outer conductor
- High RF Shielding >100 dB
- 100% Hi-pot and continuity tested
- 100% VSWR tested to max frequency of assembly
- Standard and custom lengths ship the same day

#### Configuration

Connector 1  
Connector 2  
Cable Type

SMA Male  
SMA Male Right Angle  
PE-SR402FLJ

#### Electrical Specifications

Frequency Range, GHz  
Impedance, Ohms  
Maximum VSWR  
Velocity of Propagation, %  
RF Shielding, dB  
Maximum Operating Voltage, Vrms

DC to 10  
50  
1.35:1  
69  
100  
335

#### Typical Electrical Specifications

##### Frequency 1

Frequency, MHz  
Insertion Loss

1000  
0.119 dB/ft [ 0.39 dB/m ]

##### Frequency 2

Frequency, GHz  
Insertion Loss

5  
0.28 dB/ft [ 0.92 dB/m ]

##### Frequency 3

Frequency, GHz  
Insertion Loss

10  
0.421 dB/ft [ 1.38 dB/m ]

Electrical Specification Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Right Angle Semi-Flexible Precision Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS PE39439-12](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to SMA Male Right Angle Semi-Flexible Precision  
Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS

**TECHNICAL DATA SHEET**

**PE39439-12**

**Mechanical Specifications**

**Cable Assembly**

Cable Type PE-SR402FLJ

**Temperature**

Temperature Operating Range, deg C -55 to +125

**Size**

Length, in [mm] 12 [304.8]

Diameter, in [mm] 0.161 [4.09]

Cable Color Black

One Time Minimum Bend Radius, in [mm] 0.75 [19.05]

Repeated Minimum Bend Radius, in [mm] 1.575 [40.01]

**Cable**

Center Conductor Type Solid

Cable Inner Conductor Copper, Silver

No of Shields 1

Dielectric Type PTFE

Jacket Material FEP

Jacket Diameter, in [mm] 0.161 [4.09]

**Connector 1**

Type SMA Male

Configuration Straight

**Connector 2**

Type SMA Male Right Angle

Configuration Right Angle

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Right Angle Semi-Flexible Precision Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS PE39439-12](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to SMA Male Right Angle Semi-Flexible Precision  
Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS

**TECHNICAL DATA SHEET**

**PE39439-12**

**Plotted and Other Data**

Notes:

Values at 25 °C, sea level


SMA Male to SMA Male Right Angle Semi-Flexible Precision Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Right Angle Semi-Flexible Precision Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS PE39439-12](http://www.pasternack.com/sma-male-sma-male-pe-sr402flj-cable-assembly-pe39439-12-p.aspx)

URL: <http://www.pasternack.com/sma-male-sma-male-pe-sr402flj-cable-assembly-pe39439-12-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

**PE39439-12 CAD Drawing**  
SMA Male to SMA Male Right Angle Semi-Flexible Precision  
Cable 12 Inch Length Using PE-SR402FLJ Coax, RoHS



Note: This part is lead free.

| How To Order                       |  |                |                  |             |                       |
|------------------------------------|--|----------------|------------------|-------------|-----------------------|
| Part Number Configuration          |  | Examples       |                  |             |                       |
| PE3 [zzz] [yy] - [xx] [uu]         |  | PE3000LF-100   |                  |             |                       |
| 00 - 99999                         |  | PE3000-100     |                  |             |                       |
| LF = Lead Free                     |  | PE3000LF-100CM |                  |             |                       |
| < Blank > = Standard               |  | PE3000-100CM   |                  |             |                       |
| Note: LF applies only to RF cables |  |                |                  |             |                       |
| _____ Length                       |  | Part # Ext.    | Length In Inches | Part # Ext. | Length In Centimeters |
|                                    |  | -12            | 12"              | -25CM       | 25Cm                  |
|                                    |  | -24            | 24"              | -50CM       | 50Cm                  |
|                                    |  | -36            | 36"              | -75CM       | 75Cm                  |
|                                    |  | -48            | 48"              | -100CM      | 100Cm                 |
|                                    |  | -60            | 60"              | -125CM      | 125Cm                 |
|                                    |  | -xx            | Custom Length    | -xxCM       | Custom Length         |



**PASTERNAK ENTERPRISES, INC.**  
P.O. BOX 16759, IRVINE, CA 92623  
PHONE (949) 261-1920 FAX (949) 261-7451  
WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)  
**COAXIAL & FIBER OPTICS**

DWG TITLE  
**PE39439**

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].  
4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

2231

SIZE A

SCALE N/A

CAD FILE 041912

FSCM NO. 53919

REV. -