



Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet


PE3C6379-24

Configuration

- Connector 1: N Female
- Connector 2: N Female
- Cable Type: SPF-375

Features

- Max Frequency 6 GHz
- Low PIM: -160 dBc Max
- 83% Phase Velocity
- FRPE Jacket
- 100% Tested with PIM Test Results Marked on Cable
- Lightweight and Extremely Flexible
- Low Loss with Excellent VSWR
- IP67 (when mated)
- Using Times Microwave Components



Applications

- General Purpose
- Laboratory Use
- Low PIM Applications
- Distributed Antenna Systems (DAS)
- Multi-Carrier Communication Systems
- PIM Testing

Description

Pasternack's PE3C6379-24 type N female to type N female 24 inch cable using SPF-375 coax is part of our full line of RF components available for same-day shipping. Pasternack's corrugated RF cable assemblies are ideal for applications where durability and high power are needed. This Pasternack type N to type N cable assembly has a female to female gender configuration with 50 ohm corrugated SPF-375 coax. The PE3C6379-24 type N female to type N female cable assembly operates to 6 GHz. Our low PIM design also offers excellent passive intermodulation performance with PIM levels better than -160 dBc. Times Microwave cable is used in each assembly and TMS components are used to form connections with the super flexible low PIM cable. These cable assemblies are expertly built to satisfy your specific need with high quality Times Microwave Systems manufactured parts.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts PE3C6379-24](#)



Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6379-24

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.4:1	
Velocity of Propagation		83		%
Passive Intermodulation		-165	-160	dBc
Capacitance		24 [78.74]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.5	1	2	6		GHz
Insertion Loss (Max.)	0.26	0.29	0.33	0.44		dB

Electrical Specification Notes:

PIM test results vary between cables

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Length*	24 in [609.6 mm]
Diameter	0.95 in [24.13 mm]

Cable

Cable Type	SPF-375
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	Foam PE
Number of Shields	1
Shield Layer 1	Helically Corrugated Copper Tube
Outer Conductor Material and Plating	Copper
Jacket Material	FRPE, Black
Jacket Diameter	0.435 in [11.05 mm]

One Time Minimum Bend Radius	1.75 in [44.45 mm]
------------------------------	--------------------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts PE3C6379-24](#)



Fire Rated N Female to N Female Low PIM Cable 24 Inch
Length Using SPF-375 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6379-24

Connectors

Description	Connector 1	Connector 2
Type	N Female	N Female
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Silver	Brass, Silver
Contact Plating Specification	196 µin	196 µin
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Outer Conductor Plating Specification	118 µin	118 µin
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Plating Specification	118 µin	118 µin
Torque	10 in-lbs [1.13 Nm]	10 in-lbs [1.13 Nm]

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Environmental Specifications

Temperature

Operating Range

-55 to +200 deg C

Storage Range

-55 to +200 deg C

Environmental Specification Notes:

CMR (Riser) Fire Rated

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts PE3C6379-24](#)



Fire Rated N Female to N Female Low PIM Cable 24 Inch
Length Using SPF-375 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6379-24

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts PE3C6379-24](#)



Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6379-24

How to Order

Part Number Configuration:

PE3C6379

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C6379-12 = 12 inches long cable
PE3C6379-100cm = 100 cm long cable

Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated N Female to N Female Low PIM Cable 24 Inch Length Using SPF-375 Coax Using Times Microwave Parts PE3C6379-24](https://www.pasternack.com/n-female-n-female-spf375-cable-assembly-pe3c6379-24-p.aspx)

URL: <https://www.pasternack.com/n-female-n-female-spf375-cable-assembly-pe3c6379-24-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Fire Rated N Female to N Female Low PIM Cable 24 Inch Length
Using SPF-375 Coax Using Times Microwave Parts

Technical drawing of a cable assembly. The drawing shows a cable with two connectors at the ends. The left connector is labeled "CONTACT" and the right connector is labeled "CONTACT". The cable has a "HEAT SHRINK PROTECTOR (2X)" at the left end. The main body of the cable has a "PE LABEL" and a "PIM LABEL". The "PIM LABEL" is labeled "PIM LEVEL -zzzdBc". The "PE LABEL" is labeled "www.PASTERNAK.com PART #". The cable is labeled "16mm FLATS TYP" and "SPF-375". The length of the cable is labeled "LENGTH MEASURED FROM CONTACT TO CONTACT". The cable is labeled "N FEMALE" at both ends.

Labels and dimensions shown in the drawing:

- LENGTH MEASURED FROM CONTACT TO CONTACT
- CONTACT
- CONTACT
- HEAT SHRINK PROTECTOR (2X)
- 16mm FLATS TYP
- SPF-375
- PE LABEL
- PIM LABEL
- PIM LEVEL -zzzdBc
- 6" FROM CABLE END 1 PLACE.
- 12" FROM CABLE END.
- www.PASTERNAK.com PART #
- N FEMALE
- N FEMALE

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.