



Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm  
Length Using SPF-375 Coax Using Times Microwave Parts

## RF Cable Assemblies Technical Data Sheet

**PE3C6506-100CM**

### Configuration

- Connector 1: 4.3-10 Male
- Connector 2: 7/16 DIN Male
- Cable Type: SPF-375

### Features

- Max Frequency 6 GHz
- Low PIM: -158 dBc Max
- 83% Phase Velocity
- FRPE Jacket
- 100% Tested with PIM Test Results Marked on Cable
- Lightweight and Extremely Flexible
- Low Loss with Excellent VSWR
- IP67 (when mated)
- Using Times Microwave Components

### Applications

- General Purpose
- Laboratory Use
- Low PIM Applications
- Distributed Antenna Systems (DAS)
- Multi-Carrier Communication Systems
- PIM Testing

### Description

Pasternack's PE3C6506-100CM 4.3-10 male to 7/16 DIN male 100 cm cable using SPF-375 coax is part of our full line of RF components available for same-day shipping. Pasternack's corrugated RF cable assemblies are ideal for applications where durability and high power are needed. This Pasternack 4.3-10 to 7/16 DIN cable assembly has a male to male gender configuration with 50 ohm corrugated SPF-375 coax. The PE3C6506-100CM 4.3-10 male to 7/16 DIN male cable assembly operates to 6 GHz. Our low PIM design also offers excellent passive intermodulation performance with PIM levels better than -158 dBc. Times Microwave cable is used in each assembly and TMS components are used to form connections with the super flexible low PIM cable. These cable assemblies are expertly built to satisfy your specific need with high quality Times Microwave Systems manufactured parts.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm Length Using SPF-375 Coax Using Times Microwave Parts PE3C6506-100CM](#)



Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm  
 Length Using SPF-375 Coax Using Times Microwave Parts

## RF Cable Assemblies Technical Data Sheet

**PE3C6506-100CM**

### Electrical Specifications

| Description             | Minimum | Typical    | Maximum | Units        |
|-------------------------|---------|------------|---------|--------------|
| Frequency Range         | DC      |            | 6       | GHz          |
| VSWR                    |         |            | 1.4:1   |              |
| Velocity of Propagation |         | 83         |         | %            |
| Passive Intermodulation |         |            | -158    | dBc          |
| Capacitance             |         | 24 [78.74] |         | pF/ft [pF/m] |

### Specifications by Frequency

| Description           | F1   | F2   | F3   | F4   | F5 | Units |
|-----------------------|------|------|------|------|----|-------|
| Frequency             | 0.5  | 1    | 2    | 3    |    | GHz   |
| Insertion Loss (Max.) | 0.27 | 0.34 | 0.45 | 0.52 |    | dB    |

#### Electrical Specification Notes:

PIM test results vary between cables

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1\*SQRT(FGHz) dB for the 4.3-10 connector and 0.1 dB for the 7/16 DIN connector.

### Mechanical Specifications

#### Cable Assembly

Weight 0.71 lbs [322.05 g]

#### Cable

Cable Type SPF-375  
 Impedance 50 Ohms  
 Inner Conductor Type Solid  
 Inner Conductor Material and Plating Copper Clad Aluminum  
 Dielectric Type Foam PE  
 Number of Shields 1  
 Shield Layer 1 Helically Corrugated Copper Tube  
 Outer Conductor Material and Plating Copper  
 Jacket Material FRPE, Black  
 Jacket Diameter 0.435 in [11.05 mm]

One Time Minimum Bend Radius 1.75 in [44.45 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm Length Using SPF-375 Coax Using Times Microwave Parts PE3C6506-100CM](#)



Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm  
Length Using SPF-375 Coax Using Times Microwave Parts

## RF Cable Assemblies Technical Data Sheet

**PE3C6506-100CM**

### Connectors

| Description                        | Connector 1      | Connector 2      |
|------------------------------------|------------------|------------------|
| Type                               | 4.3-10 Male      | 7/16 DIN Male    |
| Impedance                          | 50 Ohms          | 50 Ohms          |
| Contact Material and Plating       | Brass, Silver    | Brass, Silver    |
| Contact Plating Specification      | 200 µin          | 5 µin            |
| Dielectric Type                    | PTFE             | PTFE             |
| Body Material and Plating          | Brass, Tri-Metal | Brass, Tri-Metal |
| Body Plating Specification         | 80 µin           | 3 µin            |
| Coupling Nut Material and Plating  | Brass, Nickel    | Brass, Tri-Metal |
| Coupling Nut Plating Specification | 200 µin          | 3 µin            |

### Environmental Specifications

#### Temperature

Operating Range

-40 to +85 deg C

Environmental Specification Notes:

CMR (Riser) Fire Rated

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm Length Using SPF-375 Coax Using Times Microwave Parts PE3C6506-100CM](#)



Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm  
Length Using SPF-375 Coax Using Times Microwave Parts

## RF Cable Assemblies Technical Data Sheet

**PE3C6506-100CM**

### How to Order

Part Number Configuration:

**PE3C6506**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C6506-12 = 12 inches long cable  
PE3C6506-100cm = 100 cm long cable

Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm Length Using SPF-375 Coax Using Times Microwave Parts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm Length Using SPF-375 Coax Using Times Microwave Parts PE3C6506-100CM](https://www.pasternack.com/4.3-10-male-7-16-din-male-spf375-cable-assembly-pe3c6506-100cm-p.aspx)

URL: <https://www.pasternack.com/4.3-10-male-7-16-din-male-spf375-cable-assembly-pe3c6506-100cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3C6506-100CM CAD Drawing

Fire Rated 4.3-10 Male to 7/16 DIN Male Low PIM Cable 100 cm  
Length Using SPF-375 Coax Using Times Microwave Parts

