

# SHV Jack Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole



#### **PE4239**

#### Configuration

- · SHV Jack Connector
- MIL-STD-348A
- 50 Ohms

#### **Features**

- · Max. Operating Frequency 300 MHz
- Good VSWR of 1.3:1

#### **Applications**

· General Purpose Test

- Straight Body Geometry
- · Connector Interface Types: Solder Cup
- Bulkhead
- · Gold Plated Brass Contact
- · 30 µin minimum contact plating
- · Rack and Panel Mount Applications

#### Description

Pasternack's PE4239, SHV, Standard, connector with Solder Cup terminal is part of our full line of RF components available for same-day shipping. Our SHV jack connector operates up to a maximum frequency of 300 MHz and offers good VSWR of 1.3:1. This SHV bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SHV jack bulkhead connector PE4239 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### **Electrical Specifications**

| Description            | Minimum | Typical | Maximum | Units |
|------------------------|---------|---------|---------|-------|
| Frequency Range        | DC      |         | 300     | MHz   |
| VSWR                   |         |         | 1.3:1   |       |
| Operating Voltage (AC) |         |         | 3,500   | Vrms  |
| Impedance              |         | 50      |         | Ohms  |

#### **Mechanical Specifications**

Size

 Length
 1.78 in [45.21 mm]

 Width
 0.492 in [12.50 mm]

 Weight
 0.035 lbs [15.88 g]

# **Material Specifications**

| Description | Material | Plating         |
|-------------|----------|-----------------|
| Contact     | Brass    | Gold            |
|             |          | 30 μin minimum  |
| Insulation  | PTFE     |                 |
| Body        | Brass    | Nickel          |
|             |          | 100 μin minimum |



# SHV Jack Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole



### **PE4239**

## **Environmental Specifications**

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

SHV Jack Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SHV Jack Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole PE4239

URL: https://www.pasternack.com/shv-jack-standard-solder-cup-terminal-connector-pe4239-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <u>Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.</u>

