



BNC Twinax Jack Connector Solder Attachment Thru Hole PCB, .687 inch x .500 inch Hole Spacing

RF Connectors Technical Data Sheet

PE44115

Configuration

- BNC Twinax Jack Connector
- MIL-STD-348
- 78 Ohms
- Straight Body Geometry
- Thru Hole Interface Type
- Solder Attachment

Features

- Silver Plated Contact
- Contact plating according to QQ-S-365

Applications

- General Purpose Test
- PCB Applications

Description

Pasternack's PE44115 78 ohm BNC Twinax jack connector with solder attachment for thru hole PCB (.687 inch x .500 inch hole spacing) is part of our full line of RF components available for same-day shipping.

Our 78 ohm BNC Twinax jack connector PE44115 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Mechanical Specifications

Size	
Length	0.84 in [21.34 mm]
Width/Dia.	0.687 in [17.45 mm]
Height	0.687 in [17.45 mm]
Weight	0.027 lbs [12.25 g]

Material Specifications

Description	Material	Plating
Contact		Silver QQ-S-365
Insulation	PTFE	
Body	Brass	Nickel QQ-N-290

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Twinax Jack Connector Solder Attachment Thru Hole PCB, .687 inch x .500 inch Hole Spacing PE44115](#)



BNC Twinax Jack Connector Solder Attachment Thru Hole PCB, .687 inch x .500 inch Hole Spacing

RF Connectors Technical Data Sheet

PE44115

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

BNC Twinax Jack Connector Solder Attachment Thru Hole PCB, .687 inch x .500 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Twinax Jack Connector Solder Attachment Thru Hole PCB, .687 inch x .500 inch Hole Spacing PE44115](#)

URL: <https://www.pasternack.com/bnc-twinax-jack-standard-thru-hole-pcb-connector-pe44115-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE44115 CAD Drawing

BNC Twinax Jack Connector Solder Attachment Thru Hole
PCB, .687 inch x .500 inch Hole Spacing



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

DWG TITLE
PE44115

FSCM NO. 53919

2233

SIZE A

SCALE N/A

CAD FILE 061603

PE PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com