



75 Ohm RCA Male Connector Compression Attachment For Mini 59, PE-B159

TECHNICAL DATA SHEET

PE44576

75 Ohm RCA Male Connector Compression Attachment For Mini 59, PE-B159

Configuration

Connector	RCA Male
Connector Interface Type	Mini 59, PE-B159
Cable Attachment Method (Shield/Contact)	Compression
Body Style	Straight

Electrical Specifications

Impedance, Ohms	75
-----------------	----

Mechanical Specifications

Size

Length, in [mm]	1.66 [42.16]
Width/Dia., in [mm]	0.44 [11.18]
Weight, lbs [g]	0.002 [0.91]

Connector

Type	RCA Male
Contact Material and Plating	Brass, Gold
Contact Plating Specification	1μ in. minimum
Body Material and Plating	Brass, Nickel
Body Plating Specification	60μ in. minimum
Dielectric Type	Delrin

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

75 Ohm RCA Male Connector Compression Attachment For Mini 59, PE-B159 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm RCA Male Connector Compression Attachment For Mini 59, PE-B159 PE44576](http://www.pasternack.com/rca-male-standard-mini-59-connector-pe44576-p.aspx)

URL: <http://www.pasternack.com/rca-male-standard-mini-59-connector-pe44576-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE44576 CAD Drawing

75 Ohm RCA Male Connector Compression Attachment For Mini 59, PE-B159



ASSEMBLY PROCEDURES

1. STRIP CABLE AS SHOWN.
2. PUSH BRAID BACK AGAINST CABLE JACKET EVENLY.
3. INSERT CABLE INTO BODY WHILE TWISTING CONNECTOR SLIGHTLY.
4. INSERT ASSEMBLY INTO COMPRESSION TOOL & COMPRESS USING A PE5012.

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

DWG TITLE	FSCM NO. 53919	CAD FILE	011409-B	SCALE	N/A	SIZE	A	XXX
PE44576								



PASTERNAK
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com