

75 Ohm F Female Right Angle Bulkhead Mount Connector Solder Attachment Surface Mount PCB, IP67 Rated



PE44895

Configuration

- F Female Connector
- 75 Ohms
- · Right Angle Body Geometry

Features

- · Max. Operating Frequency 2.15 GHz
- Good VSWR of 1.93:1

Applications

- · General Purpose Test
- · Rack and Panel Mount Applications

- · Solder Method
- · Connector Interface Types: Surface Mount
- Bulkhead
- Tin Plated Beryllium Copper Contact
- IP67 Rated (Unmated)
- PCB Applications
- CAT\

Description

Pasternack's PE44895 type F Right Angle, F, Standard, connector with solder attachment for Surface Mount PCB is part of our full line of RF components available for same-day shipping. Our type F female connector operates up to a maximum frequency of 2.15 GHz and offers good VSWR of 1.93:1. Its right angle body geometry allows for easier connections in tight spaces. This type F bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The connector has an IP67 rating to protect against dust and temporary moisture protection under immersion conditions.

Our 75 ohm type F female right angle bulkhead connector PE44895 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.15	GHz
VSWR			1.93:1	
Insertion Loss			0.46	dB
Impedance		75		Ohms

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 1	1 to 2.15				GHz
VSWR, Max	1.43:1	1.93:1				
Insertion Loss, Max	0.2	0.46				dB

Mechanical Specifications

Size

Length 1.3 in [33.02 mm]



75 Ohm F Female Right Angle Bulkhead Mount Connector Solder Attachment Surface Mount PCB, IP67 Rated



PE44895

 Width
 0.55 in [13.97 mm]

 Height
 0.61 in [15.49 mm]

 Weight
 0.035 lbs [15.88 g]

 Mating Cycles
 500 Cycles

Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Tin	
Insulation	PTFE		
Body	Zinc	Tin	

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C
Ingress Protection (IP) Rating IP67 Rated (Unmated)

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm F Female Right Angle Bulkhead Mount Connector Solder Attachment Surface Mount PCB, IP67 Rated from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm F Female Right Angle Bulkhead Mount Connector Solder Attachment Surface Mount PCB, IP67 Rated PE44895

URL: https://www.pasternack.com/f-female-standard-surface-mount-pcb-connector-pe44895-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <u>Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.</u>

