


MCX Jack Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .059 inch Hole Spacing

PE45274



Configuration

- MCX Jack Connector
- CECC 22220
- 50 Ohms
- Right Angle Body Geometry
- Solder Method
- Connector Interface Types: Thru Hole

Features

- Max. Operating Frequency 6 GHz
- Gold Plated Beryllium Copper Contact
- 30μ in. minimum contact plating

Applications

- General Purpose Test
- PCB Applications

Description

Pasternack's PE45274 Right Angle, MCX, Standard, connector with solder attachment for Thru Hole PCB is part of our full line of RF components available for same-day shipping. Our MCX jack connector operates up to a maximum frequency of 6 GHz. Its right angle body geometry allows for easier connections in tight spaces.

Our MCX jack right angle connector PE45274 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
Operating Voltage (AC)			335	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Impedance		50		Ohms

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 1	1 to 3				GHz
VSWR, Max	1.5:1	1.63:1				


Mechanical Specifications

Size

Length	0.394 in [10.01 mm]
Width	0.236 in [5.99 mm]
Height	0.374 in [9.5 mm]
Weight	0.006 lbs [2.72 g]

MCX Jack Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .059 inch Hole Spacing

PE45274



Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold 30µ in. minimum
Insulation	Teflon	
Body	Brass	Gold 3µ in. minimum

Environmental Specifications

Temperature

Operating Range -55 to +155 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

MCX Jack Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .059 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Jack Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .059 inch Hole Spacing PE45274](#)

URL: <https://www.pasternack.com/mcx-jack-thru-hole-pcb-connector-pe45274-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE45274 CAD Drawing

MCX Jack Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .059 inch Hole Spacing

