

Mini SMP Right Angle VITA 67



RF Connectors Technical Data Sheet

PE45534

Configuration

- Mini SMP Connector
- Right Angle Body Geometry

Features

- · Max. Operating Frequency 40 GHz
- Good VSWR of 1.45:1
- · Blind Mate Connector
- · Coaxial interconnects on VPX platforms

- VITA 67 Design
- Standard MIL-STD-348 SMPM interface
- Rugged Stainless Steel construction
- Accepts 0.047" and 0.086" cable contacts for end-toend solution

Applications

- General Purpose Test
- Robust and Rugged high speed cabled solution
- VITA 67 Backplane
- High Density Applications

Description

Pasternack's PE45534 4-position block housing is part of our full line of VITA 67 Backplane solutions and is available for same-day shipping. Pasternack introduces 4 position (VITA 67.1) and 8 position (VITA 67.2) RF connector housings designed for 3U and 6U formats within the OpenVPX architecture. These blocks are machined from stainless steel for a rugged solution. The blocks are designed to accept both PE45535 (0.047" cable contact) & PE45536 (.086" cable contact) used in flexible or semi-rigid cables. These blocks are ideal for blind mating daughtercards to motherboards as the RF contacts provide +/- .010" radial misalignment tolerance and have excellent return loss up to 40 GHz.

The SMPM (Mini-SMP) blind mate connector is ideal for applications where direct visual or tactile access to the connection point is not possible, for example, when two circuit boards need to be mated. The block's right angle body geometry allows for easier connections in tight spaces.

Our SMPM (Mini-SMP) right angle block PE45534 specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		40	GHz
VSWR			1.45:1	
Dielectric Withstanding Voltage (AC)			325	Vrms
Inner Conductor DC Resistance			6	mOhms
Outer Conductor DC Resistance			5	mOhms
Insulation Resistance	5,000			MOhms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Mini SMP Right Angle VITA 67 PE45534

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



Mini SMP Right Angle VITA 67



RF Connectors Technical Data Sheet

PE45534

Mechanical Specifications

Size

 Length
 1.12 in [28.45 mm]

 Width/Dia.
 0.68 in [17.27 mm]

 Height
 0.39 in [9.91 mm]

 Weight
 0.011 lbs [4.99 g]

 Mating Cycles
 500 Cycles

Material Specifications

Body Aluminum	

Environmental Specifications

Temperature

Operating Range -65 to +150 deg C

Humidity 1,000 megohms within 5 minutes after removal from

humidity, tested per MIL-STD-202, Method 106

Shock Sawtooth pulse of 100 g 6ms per MIL-STD-202, Method

213, Condition I

Vibration MIL-STD-202, Method 214, Test Condition I, Curve D

Thermal Shock MIL-STD-202, Method 107, Test Condition A

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Mini SMP Right Angle VITA 67 PE45534



Mini SMP Right Angle VITA 67



RF Connectors Technical Data Sheet

PE45534

Mini SMP Right Angle VITA 67 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Mini SMP Right Angle VITA 67 PE45534

URL: https://www.pasternack.com/mini-smp-connector-pe45534-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE45534 CAD Drawing

Mini SMP Right Angle VITA 67

