



MCX Jack Right Angle Bulkhead Connector Solder Attachment Turret Terminal, .177 inch D Hole

TECHNICAL DATA SHEET

PE4560

MCX Jack Right Angle Bulkhead Connector Solder Attachment Turret Terminal, .177 inch D Hole

Configuration

Connector	MCX Jack
Connector Specification	IEC 60169-36, CECC 22220
Connector Interface Type	Turret
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Right Angle
Mount Method	Bulkhead

Electrical Specifications

Frequency Range, GHz	DC to 6
Impedance, Ohms	50

Mechanical Specifications

Temperature

Operating Range, deg C	-55 to +155
------------------------	-------------

Size

Length, in [mm]	0.56 [14.22]
Width/Dia., in [mm]	0.235 [5.97]
Height, in [mm]	0.375 [9.53]
Weight, lbs [g]	0.005 [2.27]

Connector

Type	MCX Jack
Contact Material and Plating	Beryllium Copper, Gold
Body Material and Plating	Brass, Gold
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Jack Right Angle Bulkhead Connector Solder Attachment Turret Terminal, .177 inch D Hole PE4560](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



MCX Jack Right Angle Bulkhead Connector Solder
Attachment Turret Terminal, .177 inch D Hole

TECHNICAL DATA SHEET

PE4560

Plotted and Other Data

Notes:

Values at 25 °C, sea level

MCX Jack Right Angle Bulkhead Connector Solder Attachment Turret Terminal, .177 inch D Hole from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Jack Right Angle Bulkhead Connector Solder Attachment Turret Terminal, .177 inch D Hole PE4560](http://www.pasternack.com/mcx-jack-right-angle-bulkhead-connector-solder-attachment-turret-terminal-.177-inch-d-hole-pe4560)

URL: <http://www.pasternack.com/mcx-jack-standard-turret-terminal-connector-pe4560-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE4560 CAD Drawing

MCX Jack Right Angle Bulkhead Connector Solder
Attachment Turret Terminal, .177 inch D Hole



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE4560

FSCM NO. 53919

SIZE A

XXXX

SCALE N/A

CAD FILE 052302

PE PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com