



2.4mm Female PCB Mount, Round Contact 50GHz  
VSWR1.25, 0.068 Inches End Launch PCB Connector

**RF Connectors**  
**Technical Data Sheet**

**PE45935**

**Configuration**

- 2.4mm Female Connector
- 50 Ohms
- Straight Body Geometry

**Features**

- Max. Operating Frequency 50 GHz
- Excellent VSWR of 1.25:1
- Gold Plated Beryllium Copper Contact

**Applications**

- General Purpose Test
- PCB Applications

**Description**

PE45935 2.4mm female PCB RF connector has a 50 Ohms impedance. Our 2.4mm female PCB connector provides a maximum frequency of 50 GHz. Our high-quality radio frequency coaxial connector is used for general purpose tests and printed circuit board applications. This 2.4mm female RF connector is stocked to be readily available for same business day shipment.

The Pasternack 2.4mm female PCB connector has a maximum VSWR of 1.25:1. The Pasternack 2.4mm PCB connector has a stainless steel body with gold plating. Our PE45935 2.4mm connector uses a gold plated-stainless steel outer conductor. Pasternack's 2.4mm female connector has a maximum operating voltage of 150 Vrms and a dielectric withstanding voltage of 500 Vrms.

Pasternack RF connector has a maximum inner conductor and outer conductor resistance of 4 mOhms and 2.5 mOhms respectively. The radio frequency connector is made from stainless steel material and has a contact life of 500 cycles or more. The Pasternack PE45935 2.4mm connector operates at a temperature range of -40 to +165 deg C. Our female RF connector with PCB termination has a 0.353 dB maximum insertion loss.

This Pasternack 2.4mm female connector will ship the same business day as purchased. Our 2.4mm female connector is part of RF, microwave, and millimeter wave components in stock for local, domestic, and international shipment. For further information on similar products, our expert technical support and trained sales team can get you the ideal RF connector as per your requirements.

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		50	GHz
VSWR			1.25:1	
Insertion Loss			0.353	dB
Operating Voltage (AC)			150	Vrms
Impedance		50		Ohms
Dielectric Withstanding Voltage (AC)			500	Vrms
Inner Conductor DC Resistance			4	mOhms
Outer Conductor DC Resistance			2.5	mOhms
Insulation Resistance	5,000			MOhms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4mm Female PCB Mount, Round Contact 50GHz VSWR1.25, 0.068 Inches End Launch PCB Connector PE45935](#)



2.4mm Female PCB Mount, Round Contact 50GHz  
VSWR1.25, 0.068 Inches End Launch PCB Connector

## RF Connectors Technical Data Sheet

**PE45935**

RF Leakage 100 dB

### Mechanical Specifications

#### Size

Length	0.50 in [12.70 mm]
Width	0.30 in [7.62 mm]
Height	0.30 in [7.62 mm]
Weight	0.00 lbs [0.45 g]
Mating Cycles	500 Cycles
Mating Torque	9.74 to 15 in-lbs [1.10 to 1.70 Nm]
Cable Retention Force	4.5 lbs 2.04 kg

### Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
Insulation	PEI	
Outer Conductor	Stainless Steel	Gold
Body	Stainless Steel	Gold

### Environmental Specifications

#### Temperature

Operating Range	-40 to +165 deg C
Humidity	MIL-STD-202, Method 106
Thermal Shock	MIL-STD-202, Method 107, Condition B
Salt Spray	MIL-STD-202, Method 101, Condition B

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4mm Female PCB Mount, Round Contact 50GHz VSWR1.25, 0.068 Inches End Launch PCB Connector PE45935](#)



2.4mm Female PCB Mount, Round Contact 50GHz  
VSWR1.25, 0.068 Inches End Launch PCB Connector

**RF Connectors**  
**Technical Data Sheet**

**PE45935**

2.4mm Female PCB Mount, Round Contact 50GHz VSWR1.25, 0.068 Inches End Launch PCB Connector from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4mm Female PCB Mount, Round Contact 50GHz VSWR1.25, 0.068 Inches End Launch PCB Connector PE45935](https://www.pasternack.com/2.4mm-female-pcb-connector-pe45935-p.aspx)

URL: <https://www.pasternack.com/2.4mm-female-pcb-connector-pe45935-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE45935 CAD Drawing

2.4mm Female PCB Mount, Round Contact 50GHz VSWR1.25,  
0.068 Inches End Launch PCB Connector

