

6

5

4


3

2

1

## REVISION

ZONE	REV.	DESCRIPTION	DATE	CHANGED BY	APPROVED BY
	A	INITIAL RELEASE	09/08/2023	BPUCHASKI	GUTTADAURO



## NOTES:

## MATERIAL:

CONNECTOR SHELL: STEEL

CONNECTOR INSULATOR: THERMOPLASTIC, UL94V-0 RATED

CONTACTS: COPPER ALLOY

## FINISH:

FRONT SHELL: NICKEL PLATED

BACK SHELL: TIN PLATED

CONTACTS: GOLD FLASH IN CONTACT AREA OVER NICKEL PLATE

SOLDER CUPS: TIN PLATED

## ELECTRICAL:

DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC rms

INSULATION RESISTANCE: 5000MΩ @ 500VDC

## MISCELLANEOUS:

OPERATING TEMPERATURE: -55°C TO +105°C

## REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELATED VERSION)

CATALOG #	PACKAGING
PE45983	1/BAG


UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

## TOLERANCES:

X = ±.2 [5]	FRACTIONS ± 1/32
.XX = ±.02 [0.5]	ANGLES ± 1°
.XXX = ±.005 [0.13]	

## CABLE LENGTH TOLERANCES:

≤12 [305]	= +1 [25] / -0
>12 [305] ≤ 60 [1524]	= +2 [51] / -0
>60 [1524] ≤ 120 [3048]	= +4 [102] / -0
>120 [3048] ≤ 300 [7620]	= +6 [152] / -0
>300 [7620]	= +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY  
AND SUBJECT TO CHANGE WITHOUT NOTICE.  
UN-DIMENSIONED/NON-CRITICAL FEATURES  
MAY VARY IN SIZE AND LOCATION  
COLORS MAY VARY**PE PASTERNAK**  
an INFINIT® brandWebsite: www.Pasternack.com  
Phone: 1.866.727.8376 | 1.949.261.1920INTERPRET ALL DIMENSIONS AND  
TOLERANCES PER ASME Y14.5

SCALE

NONE

SHEET

1 OF 1

## DESCRIPTION

SOLDER CUP D-SUB CONNECTOR, DB9 MALE

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	53919	BPUCHASKI	PE45983	A

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN  
PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED.  
THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE  
EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

6

5

4

3

2

1