

TNC Female PCB Mount Connector, 45 Degree angle with round contact 0.0394 inches diameter, 18GHz VSWR1.2



PE46002

Configuration

- TNC Female Connector
- 50 Ohms
- 45 Degree Body Geometry
- PCB

Features

- Max. Operating Frequency 18 GHz
- Excellent VSWR of 1.2:1
- Copper-Tin-Zinc Alloy Plated Beryllium Copper Contact

Applications

- General Purpose Test

Description

Pasternack's PE46002 45 Degree TNC Connector is part of our full line of RF components available for same-day shipping. Our TNC female connector operates up to a maximum frequency of 18 GHz and offers excellent VSWR of 1.2:1.

Our TNC female 45 degree PCB connector PE46002 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.2:1	
Insertion Loss			0.42	dB
Dielectric Withstanding Voltage (AC)			1,500	Vrms
Inner Conductor DC Resistance			1.5	mOhms
Outer Conductor DC Resistance			1	mOhms
Insulation Resistance	5,000			MOhms
Impedance		50		Ohms

Mechanical Specifications

Size

Length	0.898 in [22.81 mm]
Width	0.433 in [11.00 mm]
Height	1.21 in [30.73 mm]
Weight	0.015 lbs [6.8 g]
Mating Cycles	500 Cycles

TNC Female PCB Mount Connector, 45 Degree angle with round contact 0.0394 inches diameter, 18GHz VSWR1.2



PE46002

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Copper-Tin-Zinc Alloy
Insulation	Teflon	
Body	Brass	Gold over Nickel over Copper

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Humidity

MIL-STD-202, Method 106

Thermal Shock

MIL-STD-202, Method 107, Condition B

Salt Spray

MIL-STD-202, Method 101, Condition B

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

TNC Female PCB Mount Connector, 45 Degree angle with round contact 0.0394 inches diameter, 18GHz VSWR1.2 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Female PCB Mount Connector, 45 Degree angle with round contact 0.0394 inches diameter, 18GHz VSWR1.2 PE46002](#)

URL: <https://www.pasternack.com/tnc-female-connector-pe46002-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

TNC Female PCB Mount Connector, 45 Degree angle with round contact 0.0394 inches diameter, 18GHz VSWR1.2

