

## 75 Ohm BNC Female Right Angle Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .531 inch Hole Spacing



### PE4628

#### Configuration

- BNC Female Connector
- 75 Ohms
- Right Angle Body Geometry
- Connector Interface Types: Solder Cup
- 4 Hole Flange

#### Features

- Silver Plated Beryllium Copper Contact
- Contact plating according to QQ-S-365

#### Applications

- General Purpose Test
- Rack and Panel Mount Applications
- CATV

#### Description

Pasternack's PE4628 Right Angle 75 Ohm BNC Female Connector Solder Attachment for Solder Cup Cable, is part of our full line of RF components available for same-day shipping. Its right angle body geometry allows for easier connections in tight spaces. This BNC 4 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our 75 ohm BNC female right angle 4 hole flange connector PE4628 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Operating Voltage (AC)			500	Vrms
Dielectric Withstanding Voltage (AC)			1,500	Vrms
Insulation Resistance	5,000			MOhms
Impedance		75		Ohms

#### Mechanical Specifications

##### Size

Length	0.887 in [22.53 mm]
Width	0.75 in [19.05 mm]
Height	0.906 in [23.01 mm]
Weight	0.027 lbs [12.25 g]

75 Ohm BNC Female Right Angle Connector  
Solder Attachment 4 Hole Flange Solder Cup  
Terminal, .531 inch Hole Spacing



**PE4628**

**Material Specifications**

Description	Material	Plating
Contact	Beryllium Copper	Silver QQ-S-365
Insulation	Teflon	
Outer Conductor	Brass	Nickel QQ-N-290
Body	Brass	Nickel QQ-N-290

**Environmental Specifications**

<b>Temperature</b> Operating Range	-65 to +125 deg C
---------------------------------------	-------------------

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

75 Ohm BNC Female Right Angle Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .531 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm BNC Female Right Angle Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .531 inch Hole Spacing PE4628](#)

URL: <https://www.pasternack.com/bnc-female-standard-solder-cup-terminal-connector-pe4628.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE4628 CAD Drawing

75 Ohm BNC Female Right Angle Connector Solder Attachment 4 Hole  
Flange Solder Cup Terminal, .531 inch Hole Spacing

