

# SMA Female Right Angle Bulkhead Mount Commercial Grade Connector Solder Attachment Thru Hole PCB



# PE51711

#### Configuration

- · SMA Female Connector
- 50 Ohms
- · Right Angle Body Geometry

#### **Features**

· Max. Operating Frequency 18 GHz

# **Applications**

- · General Purpose Test
- · Rack and Panel Mount Applications

- · Connector Interface Types: Thru Hole
- Bulkhead
- · Commercial Grade Design
- · Gold over Nickel over Copper Plated Brass Contact
- PCB Applications

## **Description**

Pasternack's PE51711 Right Angle, SMA, Commercial Grade, connector with solder attachment for Thru Hole PCB is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 18 GHz. Its right angle body geometry allows for easier connections in tight spaces. This SMA bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SMA female right angle bulkhead connector PE51711 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50		Ohms

### **Mechanical Specifications**

0:--

Size	
Length	0.67 in [17.02 mm]
Width	0.52 in [13.21 mm]
Height	0.28 in [7.11 mm]
Weight	0.03 lbs [13.61 g]



# SMA Female Right Angle Bulkhead Mount Commercial Grade Connector Solder Attachment Thru Hole PCB



# PE51711

# **Material Specifications**

Description	Material	Plating
Contact	Brass	Gold over Nickel over Copper
Insulation	PTFE	
Body	Brass	Gold over Nickel over Copper
Coupling Nut		Gold over Nickel over Copper
		0.76µin minimum
Washer		Gold over Nickel over Copper
		0.76µin minimum

#### **Environmental Specifications**

**Temperature** 

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

SMA Female Right Angle Bulkhead Mount Commercial Grade Connector Solder Attachment Thru Hole PCB from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Right Angle Bulkhead Mount Commercial Grade Connector Solder Attachment Thru Hole PCB PE51711

URL: https://www.pasternack.com/sma-female-thru-hole-pcb-connector-pe51711-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

