

## SMA Female Bulkhead Mount Commercial Grade Connector Solder Attachment .066 inch End Launch PCB



### PE51744

#### Configuration

- SMA Female Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: .066 inch End Launch
- Bulkhead
- Commercial Grade Design

#### Features

- Max. Operating Frequency 6 GHz
- Gold Plated Beryllium Copper Contact

#### Applications

- General Purpose Test
- Rack and Panel Mount Applications
- PCB Applications

#### Description

Pasternack's PE51744 , SMA, Commercial Grade, connector with solder attachment for .066 inch End Launch PCB is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 6 GHz. This SMA bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SMA female bulkhead connector PE51744 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
Impedance		50		Ohms

#### Mechanical Specifications

##### Size


Length	0.67 in [17.02 mm]
Width	0.26 in [6.6 mm]
Height	0.26 in [6.6 mm]
Weight	0.00613 lbs [2.78 g]

#### Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
Insulation	PTFE	
Body	Brass	Gold
Washer	Phosphor Bronze	Gold

## SMA Female Bulkhead Mount Commercial Grade Connector Solder Attachment .066 inch End Launch PCB

**PE51744**



---

### Environmental Specifications

**Temperature**

Operating Range

-55 to +125 deg C

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

SMA Female Bulkhead Mount Commercial Grade Connector Solder Attachment .066 inch End Launch PCB from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female Bulkhead Mount Commercial Grade Connector Solder Attachment .066 inch End Launch PCB PE51744](#)

URL: <https://www.pasternack.com/sma-female-.066-end-launch-pcb-connector-pe51744-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE51744 CAD Drawing

SMA Female Bulkhead Mount Commercial Grade Connector Solder Attachment .066 inch End Launch PCB

