



50 Ohm 2 Watts Precision Passivated Stainless Steel TNC Female RF Load With Chain Up To 18 GHz

TECHNICAL DATA SHEET

PE6092

50 Ohm 2 Watts Precision Passivated Stainless Steel TNC Female RF Load With Chain Up To 18 GHz

Configuration

RF Load Design Precision
Connector TNC Female
Connector Specification MIL-C-39012

Heat Sink Passivated Stainless Steel

Electrical Specifications

Frequency Range, GHz DC to 18
Impedance, Ohms 50
Maximum VSWR 1.25:1
Maximum Input Power, Watts 2

Mechanical Specifications

Size

Length, in [mm] 1.338 [33.99] Width/Dia., in [mm] 0.56 [14.22]

Connector

Type TNC Female

Body Material and Plating Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

50 Ohm 2 Watts Precision Passivated Stainless Steel TNC Female RF Load With Chain Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 2 Watts Precision Passivated Stainless Steel TNC Female RF Load With Chain Up To 18 GHz PE6092

URL: http://www.pasternack.com/tnc-female-precision-termination-pe6092-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE6092 CAD Drawing

50 Ohm 2 Watts Precision Passivated Stainless Steel TNC Female RF Load With Chain Up To 18 GHz

