



Reverse Polarity SMA Male to SMA Female Right Angle Adapter

TECHNICAL DATA SHEET

PE91263

Configuration

Connector 1 SMA Male Reverse Polarity Impedance 1 50 Ohms
Connector 2 SMA Female
Impedance 2 50 Ohms
Connector Specification 2 MIL-STD-348

Connector Specification 2MIL-STD-34Adapter DesignStandardBody StyleRight Angle

Electrical Specifications

Frequency Range DC to 12.4 GHz
Maximum VSWR 1.23:1
Dielectric Withstanding Voltage, Vrms 1,500

Mechanical Specifications

Size

 Length, in [mm]
 0.62 [15.75]

 Width/Dia., in [mm]
 0.312 [7.92]

 Height, in [mm]
 0.583 [14.81]

Connector 1

Type SMA Male Reverse Polarity Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204 Coupling Nut Material and Plating Passivated Stainless Steel Coupling Nut Plating Specification QQ-P-35 Hex Size, Inch 16-May **Body Material and Plating** Passivated Stainless Steel **Body Plating Specification** QQ-P-35 Dielectric Type **PTFE**

Connector 2

Type SMA Female
Inner Conductor Material and Plating Beryllium Copper, Gold
Inner Conductor Plating Specification MIL-G-45204
Body Material and Plating Passivated Stainless Steel
Body Plating Specification QQ-P-35
Dielectric Type PTFE

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

Not RoHS Compliant

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity SMA Male to SMA Female Right Angle Adapter PE91263

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





Reverse Polarity SMA Male to SMA Female Right Angle Adapter

TECHNICAL DATA SHEET

PE91263

Plotted and Other Data

Notes:

· Values at +25 °C, sea level

Reverse Polarity SMA Male to SMA Female Right Angle Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity SMA Male to SMA Female Right Angle Adapter PE91263

URL: http://www.pasternack.com/sma-male-sma-female-right-angle-adapter-pe91263-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

PE91263 CAD DrawingReverse Polarity SMA Male to SMA Female Right Angle Adapter

