



Precision 75 Ohm F Female to F Female Adapter

RF Adapters Technical Data Sheet

PE91349

Configuration

- F Female Connector 1
- F Female Connector 2
- 75 Ohms
- Precision Design
- Straight Body Geometry

Description

Pasternack's PE91349 precision 75 ohm type F female to type F female adapter is part of our full line of RF components available for same-day shipping. Our type F to type F adapter has a female to female gender configuration in a precision design. PE91349 type F female to type F female adapter operates to 3 GHz. The Pasternack RF adapter provides good VSWR of 1.28:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.28:1	
Return Loss			18	dB
Insertion Loss			0.5	dB

Mechanical Specifications

Size	
Length	1.02 in [25.91 mm]
Width	0.5 in [12.7 mm]
Weight	0.017 lbs [7.71 g]

Description	Connector 1	Connector 2
Type	F Female	F Female
Polarity	Standard	Standard

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Precision 75 Ohm F Female to F Female Adapter PE91349](#)



Precision 75 Ohm F Female to F Female Adapter

RF Adapters Technical Data Sheet

PE91349

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	F Female		F Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Outer Conductor	Brass	Nickel	Brass	Nickel
Body	Brass	Nickel	Brass	Nickel

Compliance Certifications (see [product page](#) for current document)

Precision 75 Ohm F Female to F Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Precision 75 Ohm F Female to F Female Adapter PE91349](#)

URL: <https://www.pasternack.com/f-female-f-female-straight-adapter-pe91349-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE91349 CAD Drawing

Precision 75 Ohm F Female to F Female Adapter



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE91349

FSCM NO. 53919

2233

SIZE A

SCALE N/A

CAD FILE 021616



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com