



SMB Jack to BNC Female Adapter

RF Adapters Technical Data Sheet

PE9136

Configuration

- SMB Jack Connector 1
- BNC Female Connector 2
- 50 Ohm
- Straight Body Geometry

Features

- SMB interface compliant with MIL-C-39012
- BNC interface compliant with MIL-C-39012
- 3 μ -in minimum contact plating
- Gold Plated Brass Contact

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Pasternack's PE9136 SMB jack to BNC female adapter is part of our full line of RF components available for same-day shipping. Our SMB to BNC adapter has a jack to female gender configuration. PE9136 SMB jack to BNC female adapter operates to 4 GHz.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
Operating Voltage (AC)			335	Vrms

Electrical Specification Notes:
Values at 25°C, sea level.

Mechanical Specifications

Size

Length	1.272 in [32.31 mm]
Width	0.453 in [11.51 mm]
Weight	0.027 lbs [12.25 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to BNC Female Adapter PE9136](#)



SMB Jack to BNC Female Adapter

RF Adapters Technical Data Sheet

PE9136

Description	Connector 1	Connector 2
Type	SMB Jack	BNC Female
Polarity	Standard	Standard
Interface Specification	MIL-C-39012	MIL-C-39012

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	SMB Jack		BNC Female	
Contact	Brass	Gold 3 µ-in minimum	Brass	Gold 3 µ-in minimum
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel 70 µ-in minimum	Brass	Nickel 70 µ-in minimum

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to BNC Female Adapter PE9136](#)




SMB Jack to BNC Female Adapter

RF Adapters Technical Data Sheet

PE9136

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to BNC Female Adapter PE9136](#)



SMB Jack to BNC Female Adapter

RF Adapters Technical Data Sheet

PE9136


SMB Jack to BNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to BNC Female Adapter PE9136](#)

URL: <https://www.pasternack.com/smb-jack-bnc-female-straight-adapter-pe9136-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9136 CAD Drawing
SMB Jack to BNC Female Adapter



STANDARD TOLERANCES
.X ±0.2
.XX ±0.1
.XXX ±0.05

*STANDARD TOLERANCES APPLY
ONLY TO DIMENSIONS IN INCHES

PE PASTERNAK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE
PE9136

FSCM NO. 53919

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE 021516 SCALE N/A SIZE A 3045