



## SMA Male to MMBX Jack Push-On Adapter, with female center contact

### RF Adapters Technical Data Sheet

PE91362

#### Configuration

- SMA Male Connector 1
- Push-On MMBX Jack Connector 2
- 50 Ohms
- Straight Body Geometry

#### Features

- Max VSWR of 1.08:1 up to 12.4 GHz
- 51µ in. minimum contact plating
- Gold Plated Beryllium Copper Contact
- Reliable Snap-On connection method/Mechanical mis-alignment tolerance of 4.5°/0.7mm Max

#### Applications

- Allows Connection Between Series
- General Purpose Test
- Low cost blind mate interconnect
- Multi circuit board radios
- Board to board applications requiring multiple coaxial connections

#### Description

Pasternack's PE91362 SMA male to MMBX jack push-on adapter, is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to MMBX adapter has a male to jack gender configuration. PE91362 SMA male to MMBX jack adapter is gold plated and operates to 12.4 GHz. The Pasternack RF adapter provides excellent VSWR of 1.08:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
VSWR			1.08:1	
Insertion Loss			0.42	dB
Operating Voltage (AC)			330	Vrms
Dielectric Withstanding Voltage (AC)			500	Vrms
Insulation Resistance	1,000			MOhms

#### Mechanical Specifications

##### Size

Length	0.72 in [18.29 mm]
Width	0.315 in [8 mm]
Weight	0.011 lbs [4.99 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to MMBX Jack Push-On Adapter, with female center contact PE91362](#)



## SMA Male to MMBX Jack Push-On Adapter, with female center contact

### RF Adapters Technical Data Sheet

PE91362

Description	Connector 1	Connector 2
Type	SMA Male	MMBX Jack
Polarity	Standard	Standard
Mating Cycles	500	500
Contact Captivation Axial Force, Min	2.25 lbs [1.02 Kg]	2.25 lbs [1.02 Kg]

#### Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	SMA Male		Push-On MMBX Jack	
Contact	Beryllium Copper	Gold 51µ in. minimum	Beryllium Copper	Gold 51µ in. minimum
Insulation	PTFE		PTFE	
Outer Conductor			Beryllium Copper	Gold 8µ in. minimum
Body	Brass	Gold 8µ in. minimum	Beryllium Copper	Gold 8µ in. minimum
Coupling Nut	Beryllium Copper	Gold 51µ in. minimum		

#### Environmental Specifications

##### Temperature

Operating Range -55 to +155 deg C

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to MMBX Jack Push-On Adapter, with female center contact PE91362](#)



## SMA Male to MMBX Jack Push-On Adapter, with female center contact

### RF Adapters Technical Data Sheet

PE91362

SMA Male to MMBX Jack Push-On Adapter, with female center contact from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to MMBX Jack Push-On Adapter, with female center contact PE91362](https://www.pasternack.com/sma-male-mmbx-jack-straight-adapter-pe91362-p.aspx)

URL: <https://www.pasternack.com/sma-male-mmbx-jack-straight-adapter-pe91362-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE91362 CAD Drawing

SMA Male to MMBX Jack Push-On Adapter, with female center contact



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.1
.XXX	±0.05

\*STANDARD TOLERANCES APPLY  
ONLY TO DIMENSIONS IN INCHES



THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)

DWG TITLE

PE91362

FSCM NO. 53919

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE 093016

SCALE N/A

SIZE A

2233