

TNC Female to Female Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz



PE91789

Configuration

- TNC Jack Connector 1
- TNC Jack Connector 2

- 50 Ohms Impedance
- Radius Right Angle Body Geometry

Features

- Max VSWR of 1.2:1 up to 18 GHz
- Gold Plated Beryllium Copper Contact

Applications

- General Purpose Test

Description

The type TNC radius right angle adapter PE91789 is part of our full line of available RF, microwave, and millimeter wave components from Pasternack. Our radio frequency adapter comes with a 50 Ohm impedance and a maximum VSWR of 1.2:1. This RF adapter has a jack to jack gender configuration, which provides easier connections in tighter spaces. Our type TNC to type TNC adapter is precision manufactured to RF component industry specifications and has a maximum frequency of 18 GHz. This in-series RF adapter has a dielectric withstanding voltage of 1000 Vrms.

This type TNC jack to type TNC jack adapter is one of the many RF components that ship the same business day as they are ordered. The PE91789 jack type TNC to jack type TNC adapter has a radius right angle body. This Pasternack radius right angle type TNC coax adapter is a 90 degree swept elbow adapter. Our RF adapter is often used to enable connections between two connector types that would otherwise not mate. This RF adapter has a 1.23-inch length, 0.43-inch width, and 0.02 lbs weight.

The PE91789 adapter from Pasternack is made from a passivated stainless steel connector body and has a beryllium copper center contact. Our type TNC jack to type TNC jack radius right angle radio frequency adapter can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. This RF adapter has an operating temperature range of -65 to 165 degrees C. Additional dimensions and specifications for this in-series adapter are on our downloadable PDF datasheet above.

Pasternack has one of the largest in-stock selections of radius right angle type TNC to type TNC radio frequency adapters for international and domestic orders, including custom cable assemblies. Make your online purchase right now to take advantage of our same-business-day shipping. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the high-quality 18 GHz RF adapter that meets your requirements.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50		Ohms
VSWR			1.2:1	
Operating Voltage (AC)			500	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Inner Conductor DC Resistance			6	mOhms
Outer Conductor DC Resistance			2	mOhms
Insulation Resistance	5,000			MOhms

TNC Female to Female Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz



PE91789

Mechanical Specifications

Size

Length	1.24 in [31.47 mm]
Width	0.44 in [11.13 mm]
Height	1.24 in [31.47 mm]
Weight	0.03 lbs [13.02 g]

Description	Connector 1	Connector 2
Polarity	Standard	Standard
Mating Cycles, Min	500	500
Mating Torque	10 to 12 in-lbs 1.13 to 1.36 Nm	10 to 12 in-lbs 1.13 to 1.36 Nm
Contact Captivation Axial Force, Min	6 lbs [2.72 kg]	6 lbs [2.72 kg]

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	TNC Jack		TNC Jack	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Insulation	PTFE		PTFE	
Body	Passivated Stainless Steel		Passivated Stainless Steel	

Environmental Specifications

Temperature

Operating Range	-65 to +165 °C
-----------------	----------------

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

TNC Female to Female Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Female to Female Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz PE91789](#)

URL: <https://www.pasternack.com/tnc-jack-to-tnc-jack-right-angle-adapter-pe91789-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE91789 CAD Drawing
TNC Female to Female Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz

