

TNC Male to BNC Male Adapter



PE9179181

Configuration

- TNC Male Connector 1
- BNC Male Connector 2
- 50 Ohms Impedance
- Straight Body Geometry

Features

- Max VSWR of 1.3:1 up to 4 GHz
- Gold Plated Brass Contact

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Pasternack's PE9179181 TNC male to BNC male adapter is part of our full line of RF components available for same-day shipping. Our TNC to BNC adapter has a male to male gender configuration. PE9179181 TNC male to BNC male adapter operates to 4 GHz. The Pasternack RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
Impedance		50		Ohms
VSWR			1.3:1	
Operating Voltage (AC)			500	Vrms

Mechanical Specifications

Size

Length	0.57 in [14.48 mm]
Width	0.57 in [14.48 mm]
Height	1.26 in [32.00 mm]
Weight	0.05 lbs [20.41 g]

Description	Connector 1	Connector 2
Polarity	Standard	Standard

TNC Male to BNC Male Adapter



PE9179181

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	TNC Male		BNC Male	
Contact	Brass	Gold	Brass	Gold
Insulation	Delrin		Delrin	
Outer Conductor	Brass	Nickel	Brass	Nickel
Body	Brass	Nickel	Brass	Nickel
Gasket	PVC		PVC	
Washer	Steel	Nickel	Brass	Nickel

Environmental Specifications

Temperature

Operating Range -65 to +165 °C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

TNC Male to BNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to BNC Male Adapter PE9179181](#)

URL: <https://www.pasternack.com/tnc-male-to-bnc-male-adapter-pe9179181-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE9179181 CAD Drawing
TNC Male to BNC Male Adapter

