

C Tee Adapter Female-Male-Female



RF Adapters Technical Data Sheet

PE920

Configuration

- C Female Connector 1
- C Male Connector 2

Features

- C interface compliant with MIL-STD-348
- Contact plating according to QQ-S-365
- **Applications**
 - General Purpose Test

- 50 Ohms
- Tee Body Geometry

Silver Plated Contact

Description

Pasternack's PE9207 type C tee adapter female-male-female is part of our full line of RF components available for same-day shipping. Tee adapters (also called tee connectors) are three port devices that can be used to split or combine a signal. Unlike power dividers/combiners, however, they do not provide matched impedance at all ports.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/ disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size

Length 1.535 in [38.99 mm] Width 0.75 in [19.05 mm] Height 1.314 in [33.38 mm] Weight 0.116 lbs [52.62 g]

Description	Connector 1	Connector 2	
Туре	C Female	C Male	
Polarity	Standard	Standard	
Interface Specification	MIL-STD-348	MIL-STD-348	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: C Tee Adapter Female-Male-Female PE9207

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



C Tee Adapter Female-Male-Female



RF Adapters Technical Data Sheet

PE9207

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	C Female		C Male	
Contact		Silver		Silver
		QQ-S-365		QQ-S-365
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel		
		QQ-N-290		
Body			Brass	Nickel
				QQ-N-290
Coupling Nut			Brass	Nickel
				QQ-N-290

Compliance Certifications (see product page for current document)

C Tee Adapter Female-Male-Female from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: C Tee Adapter Female-Male-Female PE9207

URL: https://www.pasternack.com/c-female-c-male-tee-adapter-pe9207-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

PE9207 CAD Drawing

C Tee Adapter Female-Male-Female

