

TNC Male to SMC Jack Adapter



PE9226

TECHNICAL DATA SHEET

TNC Male to SMC Jack Adapter	
Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style	TNC Male 50 Ohms SMC Jack 50 Ohms Standard Straight
Mechanical Specifications	
Temperature Operating Range,deg C	-65 to +165
Size	
Length, in [mm] Width/Dia., in [mm]	1.195 [30.35] 0.59 [14.99]
Connector 1	
Type Inner Conductor Material and Plating	TNC Male Gold
Inner Conductor Plating Specification Coupling Nut Material and Plating	MIL-G-45204 Brass, Nickel
Body Material and Plating	Brass, Nickel
Dielectric Type	Teflon
Connector 2	
Type Inner Conductor Material and Plating	SMC Jack Gold
Inner Conductor Plating Specification	MIL-G-45204
Body Material and Plating Dielectric Type	Brass, Nickel Teflon
	Tenon
Compliance Certifications (visit www.Pasternack.com for c RoHS Compliant	urrent document) Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea level
URL: http://www.pasternack.com/tnc-male-smc-jack-straigh	nt-adapter-pe9226-p.aspx
TNC Male to SMC Jack Adapter from Pasternack Enterprise orders. Our RF, microwave and fiber optic products maintain a	

TNC Male to SMC Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

PE9226 CAD Drawing



