



SMA Female to 1.0/2.3 Plug Adapter

RF Adapters Technical Data Sheet

PE9691

Configuration

- SMA Female Connector 1
- 1.0/2.3 Plug Connector 2
- 50 Ohms
- Straight Body Geometry

Features

- SMA Interface compliant with MIL-STD-348
- 1.0/2.3 Interface compliant with MIL-C-39012
- Gold Plated Contact
- Contact Plating per MIL-G-45204

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Pasternack's PE9691 SMA female to 1.0/2.3 plug adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to 1.0/2.3 adapter has a female to plug gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

| | |
|-------------|---------------------|
| Size | |
| Length | 0.845 in [21.46 mm] |
| Width | 0.25 in [6.35 mm] |
| Weight | 0.006 lbs [2.72 g] |

| Description | Connector 1 | Connector 2 |
|-------------------------|-------------|--------------|
| Type | SMA Female | 1.0/2.3 Plug |
| Polarity | Standard | Standard |
| Interface Specification | MIL-STD-348 | MIL-C-39012 |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to 1.0/2.3 Plug Adapter PE9691](#)



SMA Female to 1.0/2.3 Plug Adapter

RF Adapters Technical Data Sheet

PE9691

Material Specifications

| Description | Connector 1 | | Connector 2 | |
|-----------------|------------------|---------------------|--------------|---------------------|
| | Material | Plating | Material | Plating |
| Type | SMA Female | | 1.0/2.3 Plug | |
| Contact | | Gold MIL-G-45204 | | Gold MIL-G-45204 |
| Insulation | PTFE | | PTFE | |
| Outer Conductor | Beryllium Copper | Gold MIL-G-45204 | | |
| Body | | | Brass | Nickel QQ-N-290 |

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


SMA Female to 1.0/2.3 Plug Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to 1.0/2.3 Plug Adapter PE9691](#)

URL: <https://www.pasternack.com/1.0-2.3-plug-sma-female-straight-adapter-pe9691-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9691 CAD Drawing
SMA Female to 1.0/2.3 Plug Adapter



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

| DWG TITLE | | FSCM NO. 53919 | | CAD FILE | SCALE | N/A | SIZE | A | 127 |
|-----------|--|----------------|--|----------|-------|-----|------|---|-----|
| PE9691 | | REV. - | | | | | | | |



PASTERNAK ENTERPRISES, INC.
P.O. BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451
WEB ADDRESS: www.pasternack.com
E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS