

## TNC Male to FME Jack Adapter



# RF Adapters Technical Data Sheet

PE9713

## Configuration

- TNC Male Connector 1
- FME Jack Connector 2

- 50 Ohms
- Straight Body Geometry

### **Features**

- TNC Interface compliant with MIL-STD-348A
- FME Interface compliant with MIL-STD-348A
- Gold Plated Brass Contact
- 30 µ-in min Gold Contact Plating

## **Applications**

Allows Connection Between Series

General Purpose Test

#### **Description**

Pasternack's PE9713 TNC male to FME jack adapter is part of our full line of RF components available for same-day shipping. Our TNC to FME adapter has a male to jack gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

#### **Mechanical Specifications**

Size

 Length
 1.291 in [32.79 mm]

 Width
 0.57 in [14.48 mm]

 Weight
 0.048 lbs [21.77 g]

Desc	cription	Connector 1	Connector 2
Туре		TNC Male	FME Jack
Polarity		Standard	Standard
Interface Spe	ecification	MIL-STD-348A	MIL-STD-348A

#### **Material Specifications**

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Туре	TNC Male		FME Jack	
Contact	Brass	Gold	Brass	Gold
		30 μ-in minimum		30 μ-in minimum
Insulation	PTFE		PTFE	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male to FME Jack Adapter PE9713

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



## TNC Male to FME Jack Adapter



# RF Adapters Technical Data Sheet

PE9713

Outer Conductor			Brass	Nickel	
				100 μ-in minimum	
Body	Brass	Nickel			
		100 μ-in minimum			
Gasket	Silicone				
Coupling Nut	Brass	Nickel			
		100 μ-in minimum			

#### Compliance Certifications (see product page for current document)

TNC Male to FME Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male to FME Jack Adapter PE9713

URL: https://www.pasternack.com/tnc-male-fme-jack-straight-adapter-pe9713-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

# PE9713 CAD Drawing

TNC Male to FME Jack Adapter

