

4.1/9.5 Mini DIN Male Low PIM Connector Solder Attachment for TFT-5G-402



TC-402-4195M-LP



Times Microwave Systems Connector Specification

Configuration

- 4.1/9.5 Mini DIN Male Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: TFT-5G-402
- Low PIM Design

Features

- Max. Operating Frequency 3 GHz
- Excellent VSWR of 1.15:1
- PIM levels lower than -160 dBc
- Silver Plated Brass Contact
- 5 µm contact plating
- IP 67 Rated

Applications

- General Purpose Test
- Wireless Communications
- Custom Cable Assemblies
- Low PIM Applications
- Distributed Antenna Systems (DAS)

Description

Pasternack's TC-402-4195M-LP , 4.1/9.5 Mini DIN, Low PIM, Connector is part of our full line of RF components available for same-day shipping. Our 4.1/9.5 Mini DIN male connector operates up to a maximum frequency of 3 GHz and offers excellent VSWR of 1.15:1. The 4.1/9.5 Mini DIN male connector also has low passive intermodulation of -160 dBc. The connector has an IP67 rating to protect against dust and temporary moisture protection under immersion conditions.

Our 4.1/9.5 Mini DIN male connector TC-402-4195M-LP datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.15:1	
Insertion Loss			0.1	dB
Passive Intermodulation			-160	dBc
Operating Voltage (DC)			2,000	Vdc
Inner Conductor DC Resistance			1	mOhms
Outer Conductor DC Resistance			0.5	mOhms
Insulation Resistance	5,000			MOhms
Impedance		50		Ohms

Electrical Specification Notes:
Insertion Loss is $0.1 \times \sqrt{f(\text{GHz})}$

4.1/9.5 Mini DIN Male Low PIM Connector Solder Attachment for TFT-5G-402



TC-402-4195M-LP

Mechanical Specifications

Size	
Length	0.964 in [24.49 mm]
Width	0.866 in [22.00 mm]
Height	0.866 in [22 mm]
Weight	0.03 lbs [13.61 g]
Mating Torque	106 in-lbs [[11.98 Nm]]
Cable Retention Force	33 lbs [14.97 kg]

Material Specifications

Description	Material	Plating
Contact	Brass	Silver 5 µm
Insulation	PTFE	
Body	Brass	Tri-Metal 2 µm
Coupling Nut	Brass	Nickel 5 µm
Gasket	Silicone Rubber	

Environmental Specifications

Temperature	
Operating Range	-40 to +85 deg C
Ingress Protection (IP) Rating	IP 67 Rated
Shock	IEC 60068 -2-27
Vibration	IEC 60068 -2-6-Fc
Thermal Shock	IEC 60068 -2-14-Na

Environmental Specification Notes:
Weather Standard: IEC 60068 40/085/21

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

4.1/9.5 Mini DIN Male Low PIM Connector Solder Attachment for TFT-5G-402



TC-402-4195M-LP

4.1/9.5 Mini DIN Male Low PIM Connector Solder Attachment for TFT-5G-402 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [4.1/9.5 Mini DIN Male Low PIM Connector Solder Attachment for TFT-5G-402 TC-402-4195M-LP](https://www.pasternack.com/4.1-9.5-mini-din-male-tft-402-connector-tc-402-4195m-lp-p.aspx)

URL: <https://www.pasternack.com/4.1-9.5-mini-din-male-tft-402-connector-tc-402-4195m-lp-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

TC-402-4195M-LP CAD Drawing

4.1/9.5 Mini DIN Male Low PIM Connector Solder Attachment for TFT-5G-402

