

CII

TE Internal #: 1-1617088-4


General Purpose Signal Relay, DC, Polarized, Bistable, Latching, 2 Form C DPDT-CO, 2 A Contact Rating, 26.5 VDC Coil Voltage, .72

W Coil Power

View on TE.com >



Relays & Contactors > Electromechanical Relays > DPDT Signal Relay: Magnetic-Latched, Full-Size, 2 Form C



Relay & Contactor Type: General Purpose Signal Relay

Current Type: DC

Coil Magnetic System: Polarized, Bistable, Latching

Contact Arrangement: 2 Form C DPDT-CO

Coil Termination & Connection Type

**Mechanical Attachment** 

Contact Current Rating: 2A

All DPDT Signal Relay: Magnetic-Latched, Full-Size, 2 Form C (11)

### **Features**

Product Type Features	
Relay & Contactor Type	General Purpose Signal Relay
Configuration Features	
Contact Arrangement	2 Form C DPDT-CO
Electrical Characteristics	
Coil Resistance	975 Ω
Contact Switching Voltage (Max)	28 VDC
Contact Current Rating	2 A
Coil Voltage Rating	26.5 VDC
Coil Power Rating DC	.72 W
Body Features	
Enclosure Type	Hermetically Sealed
Termination Features	
Main Termination & Connection Type	Solder Hook Terminals

Solder Hook Terminals



Product Mounting Feature Type	Flange with Mounting Holes
Product Mount Type	Panel Mount
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Vibration Resistance	30G's, 10 – 3000Hz
	30G's, 10 – 3000Hz 100G's, 6ms
Vibration Resistance	

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.



## Compatible Parts





# Customers Also Bought



## **Documents**

Product Drawings
3SAM1820A2 = M39016/32-002

English

Datasheets & Catalog Pages 5-1773450-5\_sec1\_3SAM

English