CII

TE Internal #: 1-1617146-2


General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 1 A Contact Rating, 26.5 VDC Coil Voltage, .45


W Coil Power

View on TE.com >





Relays & Contactors > Electromechanical Relays











Relay & Contactor Type: General Purpose Signal Relay

Current Type: DC

Coil Magnetic System: Non-Polarized, Monostable

Contact Arrangement: 2 Form C DPDT-CO

Contact Current Rating: 1A

Features

Product Type Features

Product Type reatures	
Relay & Contactor Type	General Purpose Signal Relay
Configuration Features	
Coil Special Features	Coil Polarity Protection Diode, Coil Suppression Diode
Contact Arrangement	2 Form C DPDT-CO
Electrical Characteristics	
Coil Resistance	1560 Ω
Contact Switching Voltage (Max)	28 VDC
Contact Current Rating	1 A
Coil Voltage Rating	26.5 VDC
Coil Power Rating DC	.45 W
Body Features	

Hermetically Sealed

Enclosure Type



Main Termination & Connection Type	Extended Leads
Coil Termination & Connection Type	Extended Leads
Mechanical Attachment	
Product Mount Type	Board Mount
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Vibration Resistance	30G's, 10 – 3000Hz
Shock Resistance	75G's, 6ms
Current Type	DC
Coil Magnetic System	Non-Polarized, Monostable

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts





Customers Also Bought TE Part #2221962-1 TE Part #2-1617032-0 TE Part #355207N001 TE Part #536013N001 A600 RCPT.SUB-ASSY, EMPTY/EMPTY HFW1201S189 = HFW 1/2 SIZE REL RT-1145-OX-24-0-CS6302 RT-1145-OX-14-0-CS6302 /24/34 TE Part #462085N002 TE Part #916511N001 TE Part #515355N002 TE Part #811112N004 RT-1145-OX-29-0-CS6302 RT-1145-OX-07-0-CS6302 RT-1145-OX-09-0-CS6302 222D142-12-0-CS6385

Documents

TE Part #195271N002

RT-1145-OX-27-0-CS6302

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1-1617146-2_J.2d_dxf.zip

TE Part #811085N003

222D163-12-0-CS6385

English

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 1 A Contact Rating, 26.5 VDC Coil Voltage, .45 W Coil Power



Customer View Model

ENG_CVM_CVM_1-1617146-2_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1617146-2_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773450-5_sec1_MGA

English

RELAY

English