


AMPLIMITE

TE Internal #: 1-1761184-1 Plug, Flat Ribbon Cable, 24 AWG, .2 mm² / .205 mm² Wire, Cableto-Board, 4 Position, 1.27 mm [.05 in] Centerline, Wire & Cable, Signal, SDL Connectors

View on TE.com >

Connectors > Audio & Video Connectors > SDL Connectors



Connector & Housing Type: Plug

Compatible With Wire & Cable Type: Flat Ribbon Cable

Wire Size: 24 AWG

Connector System: Cable-to-Board

Features

Product Type Features

| Receptacle Configuration | Standard |
|-----------------------------------|----------------|
| Connector & Housing Type | Plug |
| Connector System | Cable-to-Board |
| Connector & Contact Terminates To | Wire & Cable |



Configuration Features

| Compatible With Wire & Cable Type | Flat Ribbon Cable |
|--------------------------------------|----------------------------|
| Number of Positions | 4 |
| Body Features | |
| Shield Plating Material | Tin over Nickel |
| Shield Material | Brass |
| Contact Features | |
| Contact Mating Area Plating Material | Gold (Au) |
| Contact Base Material | Copper Alloy |
| | 50 µin |
| Contact Current Rating (Max) | 1.5 A |
| Mechanical Attachment | |
| Polarization Code | A |
| PCB Mount Retention | Without |
| Connector Mounting Type | Cable Mount (Free-Hanging) |

C For support call+1 800 522 6752

1-1761184-1

Plug, Flat Ribbon Cable, 24 AWG, .2 mm² / .205 mm² Wire, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline, Wire & Cable, Signal, SDL Connectors



Housing Features Housing Color Smoke Gray Polycarbonate GF Housing Material Centerline (Pitch) 1.27 mm[.05 in] **Dimensions** Conductor Insulation Diameter Range 1.27 mm[.05 in] Wire Size 24 AWG **Usage Conditions** Operating Temperature Range -20 - 80 °C[-4 - 176 °F] **Operation/Application Circuit Application** Signal **Product Compliance** For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU Compliant

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

Compliant

No Restricted Materials Above Threshold

| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC |
|--|---|
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

1-1761184-1

Plug, Flat Ribbon Cable, 24 AWG, .2 mm² / .205 mm² Wire, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline, Wire & Cable, Signal, SDL Connectors



Compatible Parts



Customers Also Bought



 TE Part #5205818-3
 TE Part #5205817-3
 TE Part #2-329944-6
 TE Part #2-2176392-2

 FEMALE SCREWLOCK,PLTD
 FEMALE SCREWLOCK KIT
 TWIN THREADED PLUG
 RQ 1206 221K 0.1% 10PPM 5K RL



Documents

Product Drawings 4 SDL FLAT PLUG ASSY

English

CAD Files

3D PDF

3D

1-1761184-1

Plug, Flat Ribbon Cable, 24 AWG, .2 mm² / .205 mm² Wire, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline, Wire & Cable, Signal, SDL Connectors



Customer View Model

ENG_CVM_CVM_1-1761184-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1761184-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1761184-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals UL Report

English