
1-208979-4 - ACTIVE

AMP

TE Internal #: 1-208979-4 Wire & Cable, 15 A, White, 12 AWG / 14 AWG, Nylon, 26.9 mm [1.06 in] Height, 26.9 mm [1.06 in] Width, 30.3 mm [1.19 in] Depth, Panel & PCB Outlets

View on TE.com >

Connectors > Power Connectors > Panel & PCB Outlets



Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 15 A

Housing Color: White

Wire Size: 12 AWG, 14 AWG

Housing Material: Nylon

Features

Product Type Features

Connector System

Connector & Contact Terminates To

Connectivity

Cable-to-Panel

Wire & Cable

Configuration Features

Number of Positions	3
Body Features	
Cover Color	Black
Cover Material	Nylon
Contact Features	
Contact Base Material	Brass
Contact Current Rating (Max)	15 A
Termination Features	
Termination Method to Wire & Cable	FASTON Tab
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	12.7 mm[.5 in]
Housing Color	White

C For support call+1 800 522 6752

1-208979-4

Wire & Cable, 15 A, White, 12 AWG / 14 AWG, Nylon, 26.9 mm [1.06 in] Height, 26.9 mm [1.06 in] Width, 30.3 mm [1.19 in] Depth, Panel & PCB Outlets



Housing Material	Nylon
Dimensions	
Wire Size	12 AWG, 14 AWG
Product Height	26.9 mm[1.06 in]
Product Width	26.9 mm[1.06 in]
Product Depth	30.3 mm[1.19 in]
Usage Conditions	
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Circuit Application	Power
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)

Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

C For support call+1 800 522 6752

1-208979-4

Wire & Cable, 15 A, White, 12 AWG / 14 AWG, Nylon, 26.9 mm [1.06 in] Height, 26.9 mm [1.06 in] Width, 30.3 mm [1.19 in] Depth, Panel & PCB Outlets





Customers Also Bought



Documents

Product Drawings CONV OUTLET ASSY (PUTTY WHITE)

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-208979-4_AF.2d_dxf.zip

English

3D PDF

3D

Customer View Model ENG_CVM_CVM_1-208979-4_AF.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-208979-4_AF.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages POWER_CONNECTORS_CATALOG_SEC08_AC_INPUTS

English

Instruction Sheets

Instruction Sheet (U.S.)

English

1-208979-4

Wire & Cable, 15 A, White, 12 AWG / 14 AWG, Nylon, 26.9 mm [1.06 in] Height, 26.9 mm [1.06 in] Width, 30.3 mm [1.19 in] Depth, Panel & PCB Outlets



Agency Approvals UL Report

English