TE Internal #: 1-2198318-7

zSFP+ Stacked (SFP28), Cage Assembly with Integrated Connector,

.8mm [.032in] Centerline, Signal

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > zSFP+ Stacked Cage Assembly: Gasket











Form Factor: zSFP+ Stacked (SFP28)

Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Centerline (Pitch): .8 mm [.032 in]

Sealable: No

Circuit Application: Signal

All zSFP+ Stacked Cage Assembly: Gasket (34)

Features

Product Type Features

| Cage Type | Stacked |
|----------------------------|-----------------------------------------|
| Form Factor | zSFP+ Stacked (SFP28) |
| Pluggable I/O Product Type | Cage Assembly with Integrated Connector |
| Sealable | No |

Configuration Features

| Lightpipe Style | Standard |
|---------------------------|----------|
| Number of Positions | 40 |
| Number of Ports | 2 |
| Port Matrix Configuration | 2 x 1 |

Electrical Characteristics

| Data Rate (Max) | 32 Gb/s |
|-----------------|---------|
| | |

Contact Features

| Contact Mating Area Plating Material | Gold or Gold Flash over Palladium Nickel |
|--------------------------------------|------------------------------------------|
| | |



| Tail Plating Material | Tin |
|------------------------------------------------|----------------------------|
| Contact Mating Area Plating Material Thickness | .76 μm[29.92 μin] |
| Termination Features | |
| Termination Method to PCB | Through Hole - Press-Fit |
| Termination Post & Tail Length | 1.8 mm[.07 in] |
| Housing Features | |
| Cage Material | Nickel Silver Alloy |
| Centerline (Pitch) | .8 mm[.032 in] |
| Dimensions | |
| PCB Thickness (Recommended) | 1.5 mm[.059 in] |
| Usage Conditions | |
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application | |
| Pluggable I/O Applications | zSFP+ Thermally Enhanced |
| Heat Sink Compatible | No |
| Circuit Application | Signal |
| Industry Standards | |
| UL Flammability Rating | UL 94V-0 |
| Packaging Features | |
| Packaging Method | Tray |
| Other | |
| Included Lightpipe | Yes |
| EMI Containment Feature Type | Elastomeric Gasket |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) |



| Does not contain R | REACH SVHO | |
|--------------------|------------|--|
|--------------------|------------|--|

| Halogen Content | Not Low Halogen - contains Br or Cl > 900 |
|-----------------|-------------------------------------------|
| | ppm. |

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts























Customers Also Bought

















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2198318-7_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2198318-7_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2198318-7_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

zSFP+ Interconnect Brochure

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

English

zSFP+ Stacked (SFP28), Cage Assembly with Integrated Connector, .8mm [.032in] Centerline, Signal

