1-2199230-5 ACTIVE

M.2 NGFF

TE Internal #: 1-2199230-5

4.2 mm [.165 in] Height, M Code, Gold (Au), Power, -40 – 85 °C [-40

– 185 °F], M.2 NGFF, M.2 Connectors

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > M.2 Connectors > M.2 Connectors





=TE



Connector Height: 4.2 mm [.165 in]

Connector & Keying Code: M

Contact Mating Area Plating Material: Gold (Au)

Circuit Application: Power

Operating Temperature Range: -40 - 85 °C [-40 - 185 °F]

All M.2 Connectors (29)

Features

Product Type Features

| Froduct Type realures | |
|-----------------------------------|-----------------------|
| Connector & Contact Terminates To | Printed Circuit Board |
| Connector System | Board-to-Board |
| Configuration Features | |
| Number of Positions | 67 |
| PCB Mount Orientation | Right Angle |
| Number of Rows | 2 |
| Electrical Characteristics | |
| Operating Voltage | 50 VAC |
| Body Features | |
| Primary Product Color | Black |
| Connector & Keying Code | M |

| Contact Current Rating (Max) .5 A |
|-----------------------------------|
|-----------------------------------|



| Contact Base Material | Copper Alloy |
|--|--------------------------------|
| PCB Contact Termination Area Plating Material | Gold Flash, Tin |
| PCB Contact Termination Area Plating Material Finish | Matte |
| | 15 μin |
| Contact Mating Area Plating Material | Gold (Au) |
| Termination Features | |
| Termination Method to PCB | Surface Mount |
| Mechanical Attachment | |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Housing Material | High Temperature Thermoplastic |
| Centerline (Pitch) | .5 mm[.02 in] |
| Dimensions | |
| Connector Width | 8.7 mm[.343 in] |
| Connector Length | 21.9 mm[.862 in] |
| Connector Height | 4.2 mm[.165 in] |
| Usage Conditions | |
| Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
| Operation/Application | |
| Circuit Application | Power |
| Packaging Features | |
| | |

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC |

Tape & Reel



| < 900 |
|--------|
| so BFR |
| |
| |

Solder Process Capability

Reflow solder capable to 245°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series M.2 NGFF



Customers Also Bought





TE Part #2-2484140-2 1.0mm P HPI 85deg 2x8 Pos,tin plated.

TE Part #5-2356499-8
ELCON MICRO, HEADER, R/A SMT, 12P

TE Part #2118310-2 4G WORLD BAND METASPAN TAB MT PCB BLK





TE Part #2367197-8

1.0mm WTB Side Vertical Type With
Latch

TE Part #2383586-1 CA, CCJ TO 2*Dynamic TE Part #2018697-1 SHAFT, DRIVE, BUFFER TE Part #3-2204747-8
ELCON MICRO,HEADER,R/A SMT,8P

TE Part #2401979-1 CAGE ASSY, QSFP DD 1X1, HS, LP TE Part #3-2356499-8
ELCON MICRO, HEADER, VERTICAL
SMT, 8P

Documents

Product Drawings

M.2 0.5PITCH 4.2H KEY M 15U" AU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2199230-5_B3.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2199230-5_B3.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2199230-5_B3.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

 $4.2~\mathrm{mm}$ [.165 in] Height, M Code, Gold (Au), Power, -40 – 85 °C [-40 – 185 °F], M.2 NGFF, M.2 Connectors



1-1773702-1_NGFF_QRG-EN

English

Product Specifications

Application Specification

English