1-2273104-2 ACTIVE

TE Internal #: 1-2273104-2


M12 Pigtail Cable Assembly, 4 Position, 3 m, Sensor/Actuator, A

Code, M12 Socket End A, Single Ended, Plastic

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M12 A-Code Female R/A LED Pigtail



Cable Assembly Type: M12 Pigtail

Number of Positions: 4

Cable Assembly Length: 3 m

M8/M12 Application Type: Sensor/Actuator

Connector & Keying Code: A

All M12 A-Code Female R/A LED Pigtail (16)

Features

Product Type Features

Cable Assembly Type	M12 Pigtail
Cable Assembly (End A)	M12 Socket
Configuration Features	
Configuration Number	A
Number of Positions	4
Electrical Characteristics	
Operating Voltage	24 VDC
Body Features	
Jacket Material	PVC
Connector Color (End A)	Black
Cable Color	Black
Wire Color (Base)	Brown, Blue, Black
Connector & Keying Code	A
Contact Features	
Contact Current Rating (Max)	4 A

M12

Mechanical Attachment

Thread Size



Housing Features

Housing Material	Plastic	

Dimensions

Outside Cable Diameter	4.6 mm[.181 in]
Wire Size	22 AWG

Usage Conditions

Operating Temperature Range	-30 - 80 °C[-22 - 176 °F]
Operating Temperature Range	-30 - 00 C[-ZZ - 1/0 1]

Operation/Application

Indicator Type	LED
M8/M12 Application Type	Sensor/Actuator
Shielded	No

Packaging Features

Packaging Method	Box
Packaging Quantity	25

Other

Field Serviceable	Yes
Cable Assembly Length	3 m
Cable Assembly Configuration	Single Ended

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought















Documents

Product Drawings

M12 x 1.0 angled socket pigt SH 2 LED A

English

CAD Files



3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2273104-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2273104-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2273104-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

Product Specification

English