1-2299959-1 V ACTIVE

Dynamic Series | Dynamic Series Thermocouple Connector

TE Internal #: 1-2299959-1

Connector Assembly, Housing for Female Terminals, Wire-to-Wire,

2 Position, 2.5 mm [.098 in] Centerline, Dynamic Series

Thermocouple Connector

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Connector Assembly

Connector & Housing Type: Housing for Female Terminals

Connector System: Wire-to-Wire

Number of Positions: 2

Centerline (Pitch): 2.5 mm [.098 in]

Features

Product Type Features

| Connector Product Type | Connector Assembly |
|-----------------------------------|------------------------------|
| Connector & Housing Type | Housing for Female Terminals |
| Connector System | Wire-to-Wire |
| Sealable | No |
| Connector & Contact Terminates To | Wire & Cable |
| Configuration Features | |
| Number of Positions | 2 |
| Number of Rows | 1 |
| Body Features | |
| Primary Product Color | Yellow |
| Contact Features | |
| Contact Base Material | Chromel |
| | |

Receptacle

Contact Type



Termination Features

| Termination Method to Wire & Cable | Spring Clamp |
|------------------------------------|----------------------------|
| Mechanical Attachment | |
| Mating Retention Type | Locking |
| Mating Retention | With |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Housing Features | |
| Housing Material | Thermoplastic |
| Centerline (Pitch) | 2.5 mm[.098 in] |
| Dimensions | |
| Connector Width | 22.9 mm[.9 in] |
| Connector Height | 11.05 mm[.43 in] |
| Connector Length | 15.3 mm[.6 in] |
| Usage Conditions | |
| Operating Temperature Range | -20 – 220 °C[-4 – 428 °F] |
| Industry Standards | |
| UL Flammability Rating | UL 94V-0 |
| Packaging Features | |
| Packaging Method | Tray |
| Packaging Quantity | 90 |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts















Also in the Series | Dynamic Series Thermocouple Connector









Customers Also Bought





TE Part #1-2069029-3

DYNAMIC 1500T REC HSG 9P X


BLACK



TE Part #CAT-D9934-A15B Receptacle and Tab Housing: 2.5 mm Pitch, 250V



TE Part #9-1971773-2 PTL 1X2 PLUG HSG HIGH TEMP KEY A LGR



TE Part #1871417-1
DYNAMIC D-4800 TAB HSG 8P WITH
HTS CONN



TE Part #1871419-1
DYNAMIC D-5800 TAB HSG 4P WITH
HTS CONN



TE Part #917241-8
DYNAMIC D-3500 TAB HSG 20P



TE Part #5-1971772-2
PTL 1X2 CAP PANEL MT HITEMP KEY
A LGR



TE Part #84696-1 D5000 TAB CONT S LONG REEL AU PLATING

Documents

Product Drawings

TRAY PACKAGE. THERMOCOUPLE CONN KTYPE REC

Japanese

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2299959-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2299959-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2299959-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1-1773895-2_THERMOCOUPLE_FLYER

English

Product Specifications

Product Specification

Japanese