Rail D-Sub Backshells

TE Internal #: 1-2308265-8

Quick Lock Pins, Rail D-Sub Backshells

View on TE.com >



Connectors > Connector Accessories > Connector Hardware > Quick Lock Pins for D-Sub with Threaded Inserts









-40 - 90 °C[-40 - 194 °F]



Connector Hardware Accessory Type: Quick Lock Pins

Operating Temperature (Max): 90 °C [194 °F]

Operating Temperature Range: -40 - 90 °C [-40 - 194 °F]
Hardware Accessory Function: Latching, Locking & Retention

All Quick Lock Pins for D-Sub with Threaded Inserts (10)

Features

Product Type Features

Connector Hardware Accessory Type	Quick Lock Pins
Hardware Accessory Function	Latching, Locking & Retention
Mechanical Attachment	
Thread Size	None
Usage Conditions	
Operating Temperature (Max)	90 °C[194 °F]

Product Compliance

Operating Temperature Range

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JAN 2024 (240)

SVHC > Threshold:

Pb (3.5% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Also in the Series | Rail D-Sub Backshells






Connector Contacts(5)



Connector Hardware(19)



D-Shaped Connectors(10)



D-Sub Backshells & Clamps(55)



Customers Also Bought



TE Part #926885-3 UNIV.M-N-L.PIN



TE Part #1SNA115688R2500 M6/8.SNB



TE Part #F55931-000 1966-RIBBON



TE Part #130496 PIDG SPADE



TE Part #311292-000 TMS-RJS-RIBBON-4DSCE









Documents



Product Drawings

QL SET FOR VARIANT B 8

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2308265-8_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2308265-8_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2308265-8_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Rail D-Sub Backshells Flyer

English