# 1-2325807-3 ACTIVE

### LUMAWISE | LUMAWISE LED Holders

TE Internal #: 1-2325807-3

No Driver on Board / Not Programmable / Zhaga Inspired, 60 VDC, Poke-In, 1 Position, Printed Circuit Board, LUMAWISE LED Holders,

LED Holders

View on TE.com >



Connectors > Lighting Connectors > LED Holders



Lighting Connector Features Included: No Driver on Board, Not Optic Compatible, Not Programmable, Zhaga Inspired

Operating Voltage: 60 VDC

Termination Method to Wire & Cable: Poke-In

Termination Method to Wire & Cable

Number of Positions: 1

Connector & Contact Terminates To: Printed Circuit Board

#### **Features**

### **Product Type Features**

COB Substrate Thickness	1 mm
LED Holders Product Type	LED Holder
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Lighting Connector Features Included	No Driver on Board, Not Optic Compatible, Not Programmable, Zhaga Inspired
Number of Positions	1
Electrical Characteristics	
Operating Voltage	60 VDC
Contact Features	
Contact Current Rating (Max)	3 A
Termination Features	

Poke-In



#### **Housing Features**

Housing Material	PBT GF
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





### Also in the Series | LUMAWISE LED Holders



# Customers Also Bought
























### **Documents**

### **Product Drawings**

**LUMAWISE Z45 LED HOLDER 19X19** 

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-2325807-3\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2325807-3\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2325807-3\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

**LUMAWISE Z45 LED HOLDERS** 

English

### **Product Specifications**

**Application Specification** 

English

**Application Specification** 

English

**Application Specification** 

English

**Application Specification** 

English

### Agency Approvals

**LED Holders** 

English

LED Holders CB Test Certificate to IEC 60838

English