




Connectors > Terminal Blocks & Strips > PCB Terminal Blocks



Number of Positions: 2

Terminal Block Connector Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Rows: 1

Wire Entry Angle: **90°**

Features

Product Type Features

Terminal Block Connector Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Stacking Configuration	Side Stackable
Number of Positions	2
Number of Rows	1
Wire Entry Angle	90°
Wire Entry Location	Side

Electrical Characteristics

Operating Voltage	300 VAC
-------------------	---------

Body Features

Primary Product Color	Green
Product Orientation	Vertical



Contact Features

Contact Mating Area Plating Material	Tin (Sn)
Contact Base Material	Copper
Contact Current Rating (Max)	6 A

Termination Features

Termination Method to PCB	Through Hole - Solder
Termination Method to Wire & Cable	Push-in

Housing Features

Housing Material	High Temperature Nylon or Polyester
------------------	-------------------------------------

Dimensions

Wire Size	26 – 20 AWG
-----------	-------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Method	Box & Carton
------------------	--------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2834334-2
4.0PITCH ITB CONN_2P_W
CAP_NATURAL

TE Part # 2834385-2
RELEASE POKE-IN
CONNECTOR_2P_NATURAL

TE Part # 2834006-1
RELEASE POKE-IN
CONNECTOR_1POLES

TE Part # CAT-SL36-M6642B
Miniature Headers, SlimSeal


TE Part # 2834167-3
RELEASABLE SLIM CONTACT

Also in the Series | BUCHANAN WireMate Modular Screwless


PCB Terminal Blocks(35)

Customers Also Bought






TE Part #321059
TERMINAL,SOLIS FLAG R 4 10



TE Part #9-2176422-8
TLRP 2512 3.0W R200 1% 75PPM 4K RL




TE Part #2834082-1
5.0MM SIDE ENTRY MSC 2P_GY



TE Part #8-2176554-2
3430 A2 1% 2K2 100ppm 1k RL



TE Part #1-1734264-1
M/J,RJ45,Side entry,8P8C,R/A,1



TE Part #2176555-1
3430 A2 1% 12K 100ppm 1k RL




TE Part #1-2176562-3
3430 H2 1% 3R0 150ppm 1k RL



TE Part #4-1879354-4
RR03 5% 20R AMMO



TE Part #8-1614882-5
CPF 0603 5R6 0.1% 25PPM 1K RL



TE Part #2141227-2
2POS,PIN DIA 8.0,PIN HSG,ASSY,SLD

Documents

Product Drawings
2POS 2.54MM SES CONN.

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2834016-2_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2834016-2_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2834016-2_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



[Modular Screwless Terminal Blocks Flyer \(Chinese\)](#)

[BUCHANAN WireMate Connectors Brochure](#)

[BUCHANAN WireMate Connectors Brochure](#)

[English](#)

[Modular Screwless Terminal Blocks Flyer](#)

[English](#)

Product Specifications

[Application Specification](#)

[English](#)

Instruction Sheets

[Instruction Sheet \(non U.S.\)](#)

[English](#)