

AMP | AMP Twin-Leaf

TE Internal #: 1-583718-5

Housing, Receptacle, Wire-to-Board, 40 Position, 2.54 mm [.1 in]


Centerline, Crimp, 2 Row, Black, Printed Circuit Board, Power &

Signal, AMP Twin-Leaf

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings



Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 40

Centerline (Pitch): 2.54 mm [.1 in]

Features

Product Type Features

Product Type Features	
Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Dual Positions	40
Number of Positions	40
Number of Rows	2
Body Features	
Primary Product Color	Black
Contact Features	
Contact Current Rating (Max)	5 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	

Mounting Ears

Without

Without

Panel Mount Feature Type

PCB Mount Retention

Strain Relief



Mating Retention With Connector Mounting Type Board Mount Housing Features Housing Material Polyester GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions 5.1 in Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton Packaging Ouantity 125		
Housing Features Housing Material Polyester GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions 5.1 in Usage Conditions Operating Temperature Range -55 – 105 °C[67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Mating Retention	With
Housing Material Polyester GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions 5.1 in Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Connector Mounting Type	Board Mount
Centerline (Pitch) Dimensions 5.1 in Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Packaging Features Packaging Method Carton	Housing Features	
Dimensions 5.1 in Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Housing Material	Polyester GF
Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Centerline (Pitch)	2.54 mm[.1 in]
Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Dimensions	
Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton		5.1 in
Operation/Application Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Usage Conditions	
Circuit Application Power & Signal Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Industry Standards UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Operation/Application	
UL Flammability Rating UL 94V-0 Glow Wire Rating Standard Part - Not Glow Wire Packaging Features Packaging Method Carton	Circuit Application	Power & Signal
Glow Wire Rating Packaging Features Packaging Method Carton	Industry Standards	
Packaging Features Packaging Method Carton	UL Flammability Rating	UL 94V-0
Packaging Method Carton	Glow Wire Rating	Standard Part - Not Glow Wire
	Packaging Features	
Packaging Quantity 125	Packaging Method	Carton
	Packaging Quantity	125

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | AMP Twin-Leaf



Connector Contacts(13)



Insertion & Extraction Tools(1)



Power Contacts(11)




Wire-to-Board Connector Assemblies & Housings(17)


Customers Also Bought



TE Part #326886-1 TERMINAL,PIDG R 12-10 6



TE Part #5104338-2 A/L LOW PRO HDR 14P VERT HT



TE Part #5-583853-3
TWIN LEAF TERM. STRIP CSTL



UNIV M-N-L PIN 22-18 AWG



TE Part #3-640441-5 05P MTA100 CONN ASSY WHT




TE Part #172333-1 MINI UNIVERSAL M-N-L HOUSING



TE Part #2-34080-1 PIDG SPD 22-16 COMM 22-18MIL 6





TWIN LEAF TERM. STRIP CSTL





Documents

Product Drawings

TW LEAF CRP HSG. 40-POS.

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-583718-5_AS.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-583718-5_AS.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-583718-5_AS.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL

English